



PERSONAL PROTECTION

Product Groups 957 - 963

Product Grading



Production

High performance industrial tooling designed for continuous use applications on machine tools where repeatability and long tool life are of critical importance.



Professional

Industrial tooling that has enhanced features and benefits demanded by craftsmen and professional users.



Industrial

Designed for regular use in industrial applications. Manufactured to stringent quality levels and international standards.



Standard quality tooling for use by tradesmen and generally industrial use.



Maintenance

Products designed for general maintenance of machines, workshops, garages and some household applications.



Home Improver

DIY quality tooling. Designed for home use and light industrial applications.

Contents

Description	Group	Page
Eye & Face Protection	960	794 - 799
Fall Arrest Equipment	962	814 - 815
Footware - Safety	963	828 - 831
Hand Protection	961	800 - 812
- Abrasion Resistant	961	808 - 809
- Chemical Resistant	961	812
- Disposable	961	812
- General Handling	961	802 - 807
- Puncture Resistant	961	811
- Tear Resistant	961	810
- Welders	961	811
Head Protection	957	788 - 789
Hearing Protection - Plugs	958	790
Knee Pads	962	813
Respiratory Protection - Masks	959	791 - 793
Supports & Knee Pads	962	813
Workwear	962	816 - 827
- Chemical Hazard	962	816
- Flame Resistant	962	817
- Food Industry	962	818
- Hi-Vis	962	819 - 822
- Waterproof	962	823

Protectio

Offers protection from falling impact hazards such as bricks, tools and materials. It is recommended that helmets are replaced at a maximum interval of five years. This interval should be greatly reduced for helmets that have been exposed to extensive wear and tear, left in the sun, written on or have had any labels stuck on that do not have the correct adhesive. Helmets that have been damaged i.e. cut or scratched should be replaced immediately. Helmets should be regularly inspected for damage.



Head Protection System

ABS Vented Safety Helmets

Vented safety helmets that have been designed with comfort, performance and style in mind.

8-point adjustable harness ensures a safe comfortable fit.

Conform to: EN 397: 1995.



"Mix and Match" with accessories listed below or with any other PPE to create a tailored system for all applications and trades


All items are sold separately.







Vented for wearer comfort



Manufactured from high quality materials and designed to be comfortable during prolonged periods of wear. For use (only) with Tuffsafe Vented Safety Helmets.

Conform to: EN 352-3: 2002. SNR: 2/dB.				
Description	Colour	Order Code TFF-958	Price/1 RND	
Ear Defenders	Yellow	-1250K	121.70	

Safety Visor

Price/1 RND

66.60

66.60

66.60

66.60

66.60

17.20

Order Code **TFF-957**

-1210K

-1220K

-1230K

-1240K

-1250K

-1940K

Clear, polycarbonate visor for use with Tuffsafe Visor Carrier and Vented Safety Helmets. Conforms to: EN 166 (2001). Optical class 1.

C. ZZOIIIII.		
Description	Order Code TFF-960	Price/1 RND
Polycarbonate Visor	-2840K	68.40 75.20



Ear defenders, chinstrap, visor carrier and visor supplied separately.

PERSONAL PROTECTION

Colour

White

Yellow

Blue

Red

Orange

Adjustable Chinstrap

Page **788**

| Professional | Safety Helmets



Lightweight, stable and comfortable fit with less leverage on the head and a lower centre of gravity, making it feel even lighter than it is. Short peak for enhanced visibility. The new DeFormaTec™ system reacts ultra quickly to absorb impact energy before it reaches the wearer. The helmet shell is a result of analysis of thousands of helmet crash tests. It is based on the same principle as a rigid yet flexible Formula 1 chassis, reacting on impact by partial deformation to absorb the shock. Fitted with a 4-point adjustable comfort webbing harness and absorbent soft leather sweatband. Conform to **EN 397: 1996**.



TUFFSAFE | Baseball Style Bump Caps

Protects the head against accidental scraping and bumping. Absorb energy from a blow by partial destruction or damage to the shell of the cap. It is fashionable, comfortable, breathable with the twin ventilation panels and protective. Reduced peak for increased upward vision. Washable. Adjustable strap to fit head size 58 to 62cm. Different colours available.







Colour	olour Order Code TFF-957	
Navy	-1700K	199.40
Black	-1740K	199.40

Baseball Bump Caps

Protects the head against accidental scraping and bumping. Energy from an impact is absorbed and dissipated by partial destruction or damage to the under shell of the cap. It is fashionable, lightweight and breathable. Reduced peak for increased upward vision, washable. Adjustable strap to fit head size 54 to 59cm.



Page **789**

958 HEARING PROTECTION - PLUGS, MUFFS & BANDED PLUGS

TUFFSAFE† Disposable Ear Plugs

Premium

2: 2002.

High protecting shaped foam ear plugs which provide maximum comfort with excellent attenuation, the smooth tapered finish makes fitting easier and helps form a comfortable fit. These ear plugs give evenly distributed pressure, flexibility and a good

田上

seal with optimum comfort. Conform to CE 0194 EN352-

> **PACK OF** 200_°

37dB

Pack Order Code TFF-958 Price/1 RND Quantity 200pr -0080K 710.70

Disposable Ear Plugs

Hexagonal foam plugs. Conform with EN352-2: 2002. Supplied as pairs, individually packed in polythene pouches.

Tested and approved

by **INSPEC**. Box = 200 pairs.

> **PACK OF 200**

SNR = **29dB**

H = 32dBM = 25dBL = 20dB

PERSONAL PROTECTION

Model Weight Price/1 Order Code TFF-958 Number per pk HEP029 380g -0010K 2.90

Banded Ear Plugs

Durable plastic headband equipped with soft, flexing pads adjusting to jaw and head movements. It can be worn under the chin or behind the head. Arms pivot for maximum comfort. Suitable for intermittent wear as the ear plugs do not need to be rolled to be fitted allowing

easy insertion. Can be worn under the chin or behind the head for maximum comfort SNR = **21dB** Price/1 Type TFF-958

-0200K

44.70

Ear Plug & Dispenser System

The dispenser is supplied with 1,000 TuffSafe® cordless earplugs (Refill order code: TFF-958-9020K). The dispenser is designed for durability and ease of use in the workplace. The ear plugs are dispensed singly simply by twisting the nozzle, the clear container allows the contents to be seen at

all times helping to ensure you do not unexpectedly run out of earplugs. The dispensers can either be fixed to a wall or stood on a workbench.

Ear plug specification: Cordless type, disposable for comfortable hearing protection without impairing normal communication. **SNR:** 37dB. Product

conforms to EN352-2: 2002. Nominal size: smallest: 6, largest: 12.



Price/1 RND Description TFF-958 Dispenser + 1000 Plugs Refill (1000 Plugs) -9010K 848.30 486.00 -9020K

Corded Ear Plugs

Shaped foam corded ear plugs with red cord for maximum visibility, comfort and protection, the smooth tapered finish makes fitting easier and helps form a comfortable fit. These ear plugs give evenly distributed pressure, flexibility and a good seal with optimum comfort. Conform to CE 0194 EN352-2: 2002.



Order Code Price/1 Type TFF-958 Corded Ear Plugs -0300K

Ear Defenders

Helmet Mounted

Manufactured from high quality materials and designed to be comfortable during prolonged periods of wear. Conform to: EN 352-3: 2002.

(CE, ANSI, AUS/NZ). For use with **Tuffsafe vented** safety helmets only.



Price/Pr Order Code Туре TFF-958 RND Ear Defenders -1250K 121.70

Hearina PROTECTION AT WORK Defenders

With flexible reinforced plastic headbands ABS cups and PVC cushions Conform with EN352-1: 2002



Folding Hearing Defenders

Hazardous Duty Type

Foldaway design with telescopic arms. Conform with EN352-1: 2002.



Banded

RESPIRATORY PROTECTION - MASKS: FFP3

Selection of Respiratory **Disposable Products**

There are three types of protection standards -

P1: Lower or basic level - choice with/without valve.

P2: Intermediate - choice with/without valve.

P3: Highest level of protection available only with valve. The valve reduces heat and moisture buildup which improves comfort for the

Common Respiratory Hazards

Dusts: Created when solid materials are totally or partially reduced to smaller particles, they are more easily inhaled the longer they stay

in the atmosphere.

Fumes: These will generally be created when materials/metals vapourise in high temperature conditions which then cool rapidly thus condensing into very fine particles

Gases: Which are airborne at room temperature and are able to move about rapidly into any space within a short period of time.

Vapour: Are given off by materials that are

generally liquids or solids at normal room temperature.

Terminology used in Respiratory Protection

W.E.L.: Workplace Exposure Limits These are two types - occupational exposure standards or maximum exposure limits

0.E.S.: **Occupational Exposure Standards** These are levels for a substance for which the majority of employees may be exposed to for an eight hour day, five days a week. Exposure to a substance assigned as O.E.S. can be exceeded, however steps need to have been identified to show exposure will be reduced.

M.E.L.: **Maximum Exposure Limits** These limits are generally accepted as the maximum exposure periods that people should be exposed to substances which can result in very serious types of cancer, occupational asthma etc. Exact safe levels of exposure cannot be identified, and caution should be used when exposed to these substances.

The M.E.L. should never be exceeded and exposure reduced to as low as is reasonably practicable whenever possible

Protection Factors for Respiratory Protection

N.P.F.: Nominal Protection Factor These protection factors are extracted from the performance data categories of the European Standards to which all respirators are tested. These should not be used to select R.P.E.

Assigned Protection Factor These are deduced from many workplace protection factor studies as laid out in the British Standard BS 4275. These should be used in product selection decisions

Respiratory Protective Equipment Each type of respiratory protective R.P.E.: equipment has specific limitations relevant to its use and these dictate, along with the design, what type of application and conditions are best suited to each specific product.

Particulate Respirator TUFFSAFEŤ Mask - Valved



Valved Particulate **Respirator Mask**



DRV 350

50 x NPF

Product

Number

DRV350

VALVED

Pack

Quantity

5

Weight

Order Code

TFF-959

-2140K

For protection from high toxicity solid aerosols in concentrations up to 50 x NPF or 20 x APF, the Tuffsafe FFP3 mask is designed to provide a custom fit which is comfortable for the wearer. Polypropylene outer layer provides a smooth lining and avoids loose fibres, whilst fringe seal avoids an open layer around edges. Adjustable headstrap ensures best seal with minimum leakage. Soft nose foam and adjustable nosepiece increase wearer comfort and acceptance over extended periods of use and the mask has an exhalation valve for reducing hot air build-up. Its contour design also enables compatibility with evewear and reduces fogging

Conforms to EN149:2001 + A1:2009 FFP3 NR D.

SSDRV350

Unique design to provide very low breathing resistance. Polypropylene (PP) outer layers provide smooth lining and avoid loose fibres, fringe seal avoids open layer around the edges, adjustable headstrap ensuring the best seal with minimum leakage, contour design ensures the compatibility of glasses/goggles and reduces fogging, full facial close-cell nose foam and adjustable nosepiece ensure custom shape and increase the worker comfort and acceptance. With exhalation valve for breathing easier and reduces hot air buildup. For protection from high toxicity harmful solid and liquid aerosols. Conforms to EN149 2001 and AS/NZS 1716:2003 standards.





Price/Pk

RND

RESPIRATORY PROTECTION - MASKS: FFP2

FFP2 NR D: The dolomite test is an optional test under norms **EN 149:2001 +A1:2009**. Those respirators which pass the dolomite clogging test are proved to provide a more comfortable fit and resist clogging for longer.

TUFFSAFE† Particulate Respirator Mask

DRM212

Conforms to EN149:2001 + A1:2009 FFP2 NR D.

Combines protection against harmful workplace environmental conditions with enhanced wearer comfort. Polypropylene outer layer provides smooth lining and avoids loose fibres, whilst fringe seal avoids an open layer around edges. Adjustable headstrap ensures best seal with minimum leakage. Soft nose foam and adjustable nosepiece increase wearer comfort and acceptance over extended periods of use and contour design enables compatibility with eyewear and reduces fogging. The mask is also disposable and requires no maintenance.

Protection against concentrations up to 12 x NPF or 10 x APF in materials such as calcium carbonate, china clay, cement, cellulose, sulphur, cotton, flour, ferrous metals, vegetable oils, hardwood, glass



Particle Respirator Mask - Valved DRV212

Conforms to EN149:2001 + A1:2009 FFP2 NR D.

Combines protection against harmful workplace environmental conditions with enhanced wearer comfort. Polypropylene outer layer provides a smooth lining and avoids loose fibres, whilst fringe seal avoids open layer around edges. Adjustable headstrap ensures best seal with minimum leakage. Soft nose foam and adjustable nosepiece increase wearer comfort and acceptance over extended periods of use and the mask has an exhalation value for reducing hot air build-up. Its contour design also enables compatibility with eyewear and reduces fogging.



Particulate Respirator Mask

SSDRM212

Conforms to EN149 2001 FFFP2 and AS/NZS 1716:2003.

Features polypropylene (PP) outer layers providing smooth lining and avoiding loose fibres, whilst the fringe seal avoids open layer around the edges. Kept in position by a latex-free synthetic rubber head strap. The contour design enables the mask to be worn with glasses/goggles and the close fit helps to reduce fogging. Soft close-cell nose foam and adjustable nosepiece ensures custom shape and increases worker comfort and acceptance.

For protection against low-to-average toxicity, harmful solid, liquid and smoke in concentrations up to 12 x NPF or 10 x APF.

FFP2 NR 12 x NPF 10 x APF Product Pack Weight Order Code Price/Pk RND SSDRM212 20 10g -2768D N/A

Particulate Respirator Mask - Valved SSDRV212

Conforms to **EN149 2001 FFP2 and AS/NZS 1716:2003** standards. Features polypropylene (PP) outer layers providing smooth lining and avoiding loose fibres, whilst fringe seal avoids open layer around edges. Kept in position by latex-free synthetic rubber head strap. Contour design enables mask to be worn with glasses/goggles and the close fit helps to reduce fogging. Soft close-cell nose foam and adjustable nosepiece ensure custom shape and increase worker comfort and acceptance. With exhalation valve for breathing easier and reduce hot air build-up.

For protection against low-to-average toxicity harmful solid, liquid and smoke in concentrations up to 12 x NPF or 10 x APF.



FFP1 NR D: The dolomite test is an optional test under norms EN 149:2001 +A1:2009. Those respirators which pass the dolomite clogging test are proved to provide a more comfortable fit and resist clogging for longer.

Particulate Respirator Mask

NEW

PACK OF

DRM104

Conforms to EN149:2001 + A1:2009

Combines protection against harmful v conditions with enhanced wearer com outer layer provides smooth lining and loose fibres, whilst fringe seal avoids open layer around edges. Adjustable headstrap ensures best seal with minimum leakage. Soft nose foam and adjustable nosepiece increase wearer comfort and acceptance over extended periods of use and contour design enables compatibility with evewear and reduces fogging. The mask is also disposable and

FFP1 NR D. workplace environ	nmental
fort. Polypropylend I avoids	PACK OF
an	20

FFP1 NR D

requires no maintenance.

4 x NPF

4 x APF

Product	Pack	Weight	Order Code	Price/Pk
Number	Quantity	each	TFF-959	RND
DRM104	20	8g	-2120K	N/A

Particulate Respirator Mask

NEW

Conforms to EN149:2001 + A1:2009 FFP1 NR D standards. Collapse-resistant double shell, made to withstand hot and humid conditions, a fringe seal avoids open layers around the edges, a latex-free synthetic rubber head strap and contour design ensures the mask can be worn with glasses/goggles

the close fit helps to reduce fogging. Fitted with an exhalation valve for extra comfort in hot and demanding conditions allowing easy breathing and speaking. adjustable nosepiece for a custom

Soft close-cell nose foam and shaped fit, increases the worker comfort and acceptance over extended periods of use.




FFP1 NR D 4 x NPF

Product	Pack	Weight	Order Code	Price/Pk
Number	Quantity	each	TFF-959	RND
DRV104	10	14g	-2125K	N/A

Particulate **Respirator Mask**

Conforms to EN149 2001 FFP1 standards. AS/NZS 1716:2003.

Features polypropylene (PP) outer layers providing smooth lining and avoiding loose fibres, whilst the fringe seal avoids open layer around the edges. Kept in position by a latex-free synthetic rubber head strap. The contour design enables the mask to be worn with glasses/goggles and the close fit helps to reduce fogging. Soft close-cell nose foam and adjustable nosepiece ensures custom shape and increases worker comfort and acceptance. For protection against low to average toxicity harmful solid and liquid in concentrations up to 12 x NPF



4 x APF

FFP₁

4 x NPF

Product Number	Pack Quantity	Weight each	Order Code SSF-959	Price/Pk RND
SSDRM104	20	8g	-2765K	N/A

Particulate Respirator Mask

Conforms to EN149 2001 FFP1 and AS/NZS 1716:2003

standards. Provides protection against non-toxic harmful solid and liquid in concentrations up to 4 x NPF or 4 x APF, such as calcium carbonate, china clay, cement, cellulose, sulphur, cotton, **PACK OF** flour, carbon, ferrous metals,

vegetable oils and soft wood. Recommended applications for textile industry, craftwork, iron and steel industry, mining, woodworking etc. Exhalation valve to reduce hot air build-up. Maintenance-free

FFP₁

(disposable).

4 x NPF 4 x APF

Product	Pack	Weight	Order Code	Price/Pk
Number	Quantity	each	SSF-959	RND
SSDRV104	10	14g	-2785K	N/A

'Nuisance' Dust Mask Application Information

Nuisance dust masks should not be used to protect your lungs, or used where a device complying with the European Directive 89/686 or 89/656 is required. It is not classified as a respiratory protective device and falls outside the PPE (EC Directive) Regulations. These products should not be used to protect against fine dust particles, toxic gases and vapours






960 EYE & FACE PROTECTION

Quick Reference


Through the eye and face protection range, there are a number of quick reference logos to help you choose which level of safety is right for you. Below are the logos and their meanings.


Argund

Adjustable frames for a superior fit.



unobstructed field of vision.







Polycarbonate lenses are more impact-resistant and lighter than most types of lens.



Has a lower impact energy rating and is more flexible compared to polycarbonate.



This provides increased safety, while retaining excellent visibility.



Adjustable

Frame

uare

Wrap

Argund

Gives a level of protection against harmful UV rays.



Extended brow guard moulded into the top of the lens gives a near perfect orbital seal against debris.



For greater protection from debris towards the side of the eyes.



Glasses which have a larger lens to cover the cheek bone.



Resistant to chemical splashes not chemical proof.



Hard coated for excellent durability and scratch resistance resulting in unobstructed viewing.



Anti-Mist Safety Spectacles

Saturn

One-piece clear polycarbonate lens with anti-mist treatment. Lightweight black nylon frame with built-in brow guard. Built-in side protection with integral nose bridge and adjustable





Lens	Frame	Order Code	Price/1
Type	Colour	SSF-960	RND
Clear	Black	-7610K	52.60

Anti-Mist Safety Spectacles

Voyager

Two piece clear polycarbonate lenses with anti-mist treatment. Built-in brow guard and side shields with integral nose bridge. Low energy impact protection with total UV protection. Class 1.



icratet



Lens Type	Frame Colour	SSF-960	RND
Clear	Black	-8200K	23.40

Anti-Mist Safety Spectacles

Apollo

One piece amber tinted polycarbonate lens with anti-mist treatment and ultra lightweight design (26g). Built-in side protection with soft silicone nose bridge and adjustable temple length. Low energy impact protection with total UV protection. Hang cord attachment points. Class 1.



Lens Type	Frame Colour	Order Code SSF-960	Price/1 RND
Amber tinted	Black	-5200K	20.00

Anti-Scratch/Anti-Mist

Safety Spectacles



Low energy impact protection. Ultra light anallergenic frame with low friction length adjustment at the temples and front angle adjustment. Class 1 optical quality. Arms have hang cord attachment



Lens Frame Type Colour Anti-Scratch/Fog Black

Price/1 Order Code KEN-960 RND 104.70

Over Spectacles

PROTECTION

PERSONAL

Totally polycarbonate over spectacles with built-in side shields and brow guard and no metallic parts. Low energy impact protection at extreme environmental temperatures with UV protection. Can be worn

over most glasses. Hang cord attachment points. Class 1



EN166 F		
Lens	Frame	Order Code
Type	Colour	SSF-960
Clear	Clear	-0800K

Scratch Resistant Safety Spectacles

Lens

Side

Adjustable

Frame

points.

UV protection against electrical arc discharges caused by a short circuit.



Price/1 Type Colour KEN-960 82.70 13.40 Clear Blue -8050K

Anti-Mist/Scratch Resistant Safety Spectacles

Clear single wide angle lens for an unobstructed field of vision and protection against low energy impacts from the front and side. Impact protection at extreme temperatures. Built-in side protection for added safety, ultra lightweight design with brow guard and soft nose pads and temple ends for a comfortable fit. Class 1 optical quality for distortion-free continuous use.



Lens Type	Model	Order Code TFF-960	Price/1 RND
Clear	Imola	-3740K	48.40

Anti-Mist/Scratch Resistant Safety Spectacles

Le Mans

Frameless safety spectacles with a clear single wide angle lens for an unobstructed field of vision and protection against low energy impacts from the front and side. Impact protection at extreme temperatures. Ultra lightweight design. Class 1 optical quality for distortion free continuous use. Conform to: EN 166 EN 170.



Scratch Resistant/Anti-Mist Safety Spectacles

Leopard

Low energy impact protection. No metallic parts. Polycarbonate one piece frame with adjustable temple length, built-in brow guard and built-in side shields for increased lateral protection. Class 1 optical quality. Ultra lightweight design.



Anti-Mist Safety Spectacles

One piece clear polycarbonate lens with anti-mist treatment

with integral nose bridge adjustable temple length and lens

and ultra lightweight design (26g). Built-in side protection

inclination. Low energy impact protection with total UV

protection. Hang cord attachment points. Class 1.



Anti-Mist Safety Spectacles

Mercury

One-piece clear polycarbonate lens. Lightweight black nylon frame with built-in brow guard. Integral nose bridge and adjustable temple length. Low energy impact protection. Class 1.



.ens





Clear

Safety Spectacles

Strata

Lens

A twin lens wrap around safety spectacle with hard coated lenses and burgundy soft frame coating for comfort and fit.



-7430K

116.50

Anti-Mist Safety Spectacles

Wrap around safety spectacles have wide angle clear lens that provide a sharp clear view and protect against low energy impacts. UV protection, anti-mist and scratch resistant lens, ultra lightweight twin lens design. Brow ventilation with soft nose pads and temple ends for a comfort. Low energy impact protection at extreme

temperatures. Class 1 optical quality for distortion free continuous use. Conform to: EN 166 EN 170.

Lens Colour	Model	Order Code TFF-960	Price/1 RND
Amber	Silverstone	-3600K	50.00

Anti-Mist/Scratch Resistant Safety Spectacles

The wide angle single-piece lens provides low energy impact protection without obscuring field of view. Ultra lightweight design. Class 1 optical quality for distortion-free continuous use. Conform to:

EN 166 EN 170.

Order Code TFF-960 Price/1 RND Lens Model Colour -3720K 48.40 Davtona Grey

Anti-Mist/Scratch Resistant Safety Spectacles

Monaco

The wide angle single-piece lens provides low energy impact protection without obscuring field of view.

UV protection, anti-mist and cratch resistant lens, ultra lightweight design.

Class 1 optical quality for distortion free continuous use. Conform to: EN 166 EN 170.

Lens	Model	Order Code	Price/1
Colour		TFF-960	RND
Clear	Monaco	-3700K	48.40

Safety Spectacles

PROTECTION

PERSONAL

Wide angle lens and impact protection at extreme temperatures. Scratch resistant. Ultra lightweight design. Anti-mist treatment. Class 1 optical quality for distortion-free continuous use. Rubber end tips and nose bridge for user





Lens Colour	Model
Clear	Star

Price/1 TFF-960 RNĎ -3860K 45.60

Anti-Mist Safety Spectacles

Europa

Wrap

Annumed A

Two-piece black polycarbonate wrap around lenses providing low energy impact protection, total UV protection, an anti-mist coating. The ultra lightweight high strength frame has a soft silicone nose bridge and adjustable temple length to ensure user comfort.

Hang cord attachment points. Class 1.



Argund

Wrap

Argund

Wrap

Around

Wrap

Argund

Lens

Frame/Lens	Model	Order Code	Price/1
Colour		SSF-960	RND
Black	Europa	-5420K	25.00

Scratch Resistant Safety Spectacles

Black one-piece design with wrap around scratch resistant lenses giving low impact protection and UV protection for



Frame/Lens	Model	Order Code	Price/1
Colour		SSF-960	RND
Black	Astrid	-7800K	20.00
Yellow	Cassini	-7820K	20.00

Scratch Resistant Safety Spectacles

One-piece wrap around polycarbonate spectacle which is light in weight and features hard coated anti-mist and scratch





Frame/Lens	Model	Order Code	Price/1
Colour		SSF-960	RND
Clear	Zenith	-8400K	21.70
Yellow	Mir	-8420K	21.70

Safety Spectacles

Andromeda

Single clear wrap around polycarbonate lens, scratch resistant, low impact protection and UV protection.



Lens	Model	Order Code	Price/1
Colour		SSF-960	RND
Clear	Andromeda	-7830K	67.50

23.40

Wrap

Argund

Lens

SITESAFE.

Anti-Mist Safety Spectacles

Challenger

Two-piece clear polycarbonate lens with anti-mist treatment and ultra lightweight design (26g). Built-in side protection with soft silicone nose bridge and adjustable temple length.



-5400K

Anti-Mist Safety Spectacles

Retro-R

Moulded one-piece wrap around polycarbonate anti-mist lens with multi-adjust, soft, non-allergenic nose bridge. No frame means maximum unobstructed peripheral vision. Side arms also feature lateral adjustment for maximum versatility and comfort. Supplied with neck cord.

Black

CE approved to **EN166F**.



Lens	Frame	Order Code	Price/1
Type	Colour	SSF-960	RND
Polycarbonate	Blue	-7400K	33.40

Soft Spectacle Case & Spectacle Neck Cord



Туре	Order Code KEN-960	Price/1 RND
Soft Spectacle Case	-9560K	70.20
Spectacle Neck Cord	-9620K	34.70

TUFFSAFE† Anti-Mist Safety Goggles

XL21

Safety goggles with clear single-piece polycarbonate lens and anti-mist coating. Mounted in a PVC housing with easy flow indirect ventilation and adjustable elasticated strap.






	_		
Description	Frame Colour	Order Code TFF-960	Price/1 RND
Goggles	Clear	-1250K	81.70

SITESAFE Safety Goggles

Designed to protect the wearer from eye injury against moderate unspecified mechanical impact hazards. Anti-dust and impact resistant. Direct ventilation.







 Optical Class
 1

 Mechanical Strength
 B

 Frame Colour
 Weight each
 Order Code SF-960
 Price/1 RND

 Green
 80g
 -0520K
 15.00

(€ ♥ EN166

▼ Scratch Resistant/ Anti-Mist Safety Goggles

All goggles have a wide field of vision, built-in brow and cheek protection, soft PVC frame with an anatomically shaped bridge to adapt to all faces. All lenses provide UV protection. All frames will protect against liquid droplets and/or splashes. Fitted with wide anallergic elastic headbands and a one-piece replaceable scratch resistant, anti-mist clear

Tiger

Medium energy impact protection. Smoke coloured frame with a polycarbonate lens and are lined with soft foam for user comfort and increased adherence. The lens is resistant to molten metals and hot solids (splashes of molten metals and penetration of hot solid). The frame has an indirect ventilation system and is resistant to liquids (drops and











Anti-Gas/Flame Resistant Safety Goggles

Medium energy impact protection. Suitable for foundry work. The frame, lens and elastic strap are manufactured from flame resistant material. Fitted with a flexible nose bridge to adapt to all faces. Large peripheral viewing area. One piece 2mm anti-mist, scratch resistant, clear polycarbonate lens with an extra wide elastic headband. Can be fitted over most prescription glasses. The frame is resistant to liquids (drops and splashes), gross particles (dust particles >5 microns), gas and fine particles (gas vapours, splashes, smokes and dust particles <5 microns and molten metals and hot solids (splashes of molten metals and penetration of hot solids).













Lens Type	Frame Colour	Order Code KEN-960	Price/1 RND
Scratch Resistant	Red	-8130K	340.50
Spare Lens		-8120K	126.20

splashes) and penetration of hot solids. **Foam Face Seal**

Order Code KEN-960

-8140K

Clear framed goggles are resistant to gross particles (dust particles >5 microns) and gas and fine particles (gas vapours, splashes, smokes and dust particles <5 microns.

Frame

Colour

Smoke

Scorpion

Lens Type

(Scratch resistant)

Polycarbonate

Medium energy impact protection. Clear frame with a 2mm thick polycarbonate lens. The lens and the frame is resistant to molten metals and hot solids (splashes of molten metals and penetration of hot solids).

PERSONAL PROTECTION

Low energy impact protection at extreme temperatures. Clear frame with an extremely flexible acetate lens.



Price/1 RND

247.60





Cheek

Guard

Scratch Resistant/Anti-Mist Safety Goggles

Low energy impact protection at extreme temperatures. UV protection against electrical arc discharges caused by a short circuit. Ultra light nylon frame with length adjustment the temples and front angle adjustment for low friction, lined with soft foam for user comfort and increased adherence. One-piece, scratch resistant, anti-mist clear polycarbonate lens. As well as the arms having hang cord attachment points, a black universal hang cord is included with the goggles. Resistant to liquids (drops and splashes) and gross particles (dust particles >5 microns).











-8060K

225.90





🔽 Scratch Resistant/ Anti-Mist Safety Goggles

All goggles have a wide field of vision, built-in brow and cheek protection, soft PVC frame with an anatomically shaped bridge to adapt to all faces. All lenses provide UV protection. All frames will protect against liquid droplets and/or splashes. Fitted with wide anallergic elastic headbands and a one-piece replaceable scratch resistant, anti-mist clear



Medium energy impact protection. Smoke coloured frame with a polycarbonate lens and are lined with soft foam for user comfort and increased adherence. The lens is resistant to molten metals and hot solids (splashes of molten metals and penetration of hot solid). The frame has an indirect ventilation system and is resistant to liquids (drops and









Medium energy impact protection. Suitable for foundry work. The frame, lens and elastic strap are manufactured from flame resistant material. Fitted with a flexible nose bridge to adapt to all faces. Large peripheral viewing area. One piece 2mm anti-mist, scratch resistant, clear polycarbonate lens with an extra wide elastic headband. Can be fitted over most prescription glasses. The frame is resistant to liquids (drops and splashes), gross particles (dust particles >5 microns), gas and fine particles (gas vapours, splashes, smokes and dust particles <5 microns and molten metals and hot solids (splashes of molten metals and penetration of hot solids).

Anti-Gas/Flame Resistant Safety Goggles













Lens Type	Frame Colour	Order Code KEN-960	Price/1 RND
Scratch Resistant	Red	-8130K	340.50
Spare Lens		-8120K	126.20

splashes) and penetration of hot solids. Foam Face Seal

Order Code **KEN-960**

-8140K

Clear framed goggles are resistant to gross particles (dust particles >5 microns) and gas and fine particles (gas vapours, splashes, smokes and dust particles <5 microns.

Frame

Colour

Smoke

Scorpion

Lens Type

(Scratch resistant)

Polycarbonate

Medium energy impact protection. Clear frame with a 2mm thick polycarbonate lens. The lens and the frame is resistant to molten metals and hot solids (splashes of molten metals and penetration of hot solids).

I ion

PERSONAL PROTECTION

Low energy impact protection at extreme temperatures. Clear frame with an extremely flexible acetate lens.



Price/1 RND

247.60



cratch

Wide

Scratch Resistant/Anti-Mist Safety Goggles

Low energy impact protection at extreme temperatures. UV protection against electrical arc discharges caused by a short circuit. Ultra light nylon frame with length adjustment the temples and front angle adjustment for low friction, lined with soft foam for user comfort and increased adherence. One-piece, scratch resistant, anti-mist clear polycarbonate lens. As well as the arms having hang cord attachment points, a black universal hang cord is included with the goggles. Resistant to liquids (drops and splashes) and gross particles (dust particles >5 microns).



Lens







EN166 EN170				Headban
Type	Lens (Scratch resistant)	Frame Colour	Order Code KEN-960	Price/1 RND
Scorpion	Polycarbonate	Clear	-8070K	139.50
Lion	Acetate	Clear	-8080K	162.90
A !				

Accessories		
Spare Lens	Order Code	Price/1
Type	KEN-960	RND
Polycarbonate	-8100K	116.90
Acetate	-8110K	116.90







nd Protecti

The wearing of hand protection in hazardous areas is a requirement under regulation 4 of the personal protective equipment at work regulations 1992. This regulation requires employers to provide suitable personal protective equipment to employees exposed to health and safety risks. Gloves protect your hands from hazards such as burns, freezing, electrocution, abrasions, contusions, lacerations and skin complaints such as dermatitis. Gloves should be checked regularly inside and out for any contamination and wear as this can reduce the protection rating of the glove below the standard given. We recommend regular replacement as the best form of protection.

Glove Standards & Types

Simple Design (Category 1)

Gloves with this designation offer protection against light cuts, contusions, abrasions and mild detergents. Suitable for areas of 'minimal risk' where the effects on hands without gloves would be easily reversible or superficial. These products are unmarked and self-certified.

Intermediate Design (Category 2)

Gloves with this designation offer protection against heavier cuts, contusions, abrasions, tears and punctures. Suitable for areas of specific risk: abrasion, blade cuts, tear and puncture. The performance of the glove against these risks is listed below the symbol as shown

Complex Design (Category 3)

For areas/applications that can seriously or irreversibly harm the health. Such products, in addition to the CE type test, will also have to be either produced under an approved quality system OR be typed tested on an annual basis.

BS EN388 Mechanical Hazard Gloves

Mechanical hazards are associated with handling rough or sharp objects that could damage skin such as brick, concrete, glass, and sheet metal. Mechanical hazards are not associated with moving machinery. Gloves can be a hazard if there is a possibility they could snag in moving parts and put the user in danger.

Abrasion Resistant Gloves



a) Abrasion resistance. Scale 1 (low) to 4 (high).

b) Cut resistance. Scale 1 (low) to 5 (high).

c) Tear resistance. Scale 1 (low) to 4 (high).

d) Puncture resistance. Scale 1 (low) to 4 (high). 0 = Fail. X = No test carried out.

Each Abrasion Resistant

glove has a rating - the higher the number, the greater the protection.









Cut Resistant Gloves.



a. **b.** c. d.

a) Abrasion resistance. Scale 1 (low) to 4 (high).

b) Cut resistance. Scale 1 (low) to 5 (high).

Tear resistance. Scale 1 (low) to 4 (high). d) Puncture resistance. Scale 1 (low) to 4 (high).

0 = Fail. X = No test carried out.

Each Cut Resistant glove has a rating - the higher the number, the greater the protection.











Tear Resistant Gloves



a) Abrasion resistance. Scale 1 (low) to 4 (high).

Cut resistance. Scale 1 (low) to 5 (high).

c) Tear resistance. Scale 1 (low) to 4 (high).

d) Puncture resistance. Scale 1 (low) to 4 (high). 0 = Fail. X = No test carried out.

Each Tear Resistant glove has a rating - the higher the number, the greater the protection.









Puncture Resistant Gloves



- a) Abrasion resistance. Scale 1 (low) to 4 (high).
- b) Cut resistance. Scale 1 (low) to 5 (high).
- c) Tear resistance. Scale 1 (low) to 4 (high).

d) Puncture resistance. Scale 1 (low) to 4 (high).

0 = Fail. X = No test carried out.

Each Puncture Resistant glove has a rating - the higher the number, the greater the protection.









BS EN374 Chemical Hazard Gloves

Gloves with this designation offer protection against chemical splash, immersion and micro organism hazards. With the wide variety of chemicals used in today's industries any doubt with the suitability of gloves contact your local branch.



A 'Chemical Resistant' glove with a breakthrough time greater than 30 minutes. The identification letters of 3 chemicals against which the glove was tested will also appear next to the EN number.

A 'Low Chemical Resistant' glove that has failed to achieve the 30 minute breakthrough time. No chemical identification letters are shown.

Micro Organism

BS EN511 Thermal Hazard (Cold) Gloves

Gloves with this designation offer protection against convective and contact cold hazards.



- a) Convective cold resistance. Scale 0 (low) to 4 (high).
- b) Contact cold resistance. Scale 0 (low) to 4 (high).
 - c) Water permeability resistance. Scale 0 (low) to 4
- **a. b. c.** 0 = Fail. X = No test carried out.

BS EN407 Thermal Hazard (Heat) Gloves

Gloves with this designation offer protection against fire, contact heat, convective heat, radiant heat and molten metal.



- a) Burning behaviour resistance. Scale 0 (low) to 4 (high).
- b) Contact heat resistance. Scale 0 (low) to 4 (high).
- c) Convection heat resistance. Scale 0 (low) to 4 (high). d) Radiation heat resistance. Scale 0 (low) to 4 (high).
- e) Small splash molten resistance. Scale 0 (low) to 4 (high).
- f) Large quantity molten resistance. Scale 0 (low) to 4 (high).
- a.b.c.d.e.f. 0 = Fail. X = No test carried out.

Contact Heat Test

A sample is taken from the palm of the glove. The outside of the glove is put on a hot surface and the temperature of the inside of the glove is monitored. The temperature on the inside of the palm sample must not rise by more than 10°C above room temperature for a minimum of 15 seconds.

Performance Scale	Contact temperature	Threshold time
1	100°C	>15 Seconds
2	250°C	>15 Seconds
3	350°C	>15 Seconds
4	500°C	>15 Seconds

Food Symbol



Products that carry the food contact symbol are suitable for use with all food categories (Dry foods, aqueous foods, acidic foods, alcoholic foods and fatty foods). This has been established through conducting tests according to the draft European Standards for food contact migration DD ENV 1186 series.

GROUP

Ouick Reference

Through the hand protection range, there are a number of quick reference logos to help you choose which level of safety is right for you. Below are the logos and their meanings.



Deters oil and grease and resists oil soak up where oil saturated gloves are a problem in many fabrication plants.



Material is resistant to abrasions for greater protection.



Offers protection against the level of voltage.



Open backed gloves provide extra ventilation to the hand keeping it cooler throughout long periods of use.



Offers extra protection against low impact on the base of the wrist.



Added surface to provide extra grip during application.



Help prevent and relieve pain associated with RSI (repetitive strain injury).



Resists the build-up and conductance of static electricity. Of most benefit when walking on synthetic carpets or near electrical machinery.



Handling intermittently hot objects and materials in high-heat environments.



Offers extra protection against low impact on the wrist or forearm.



Designed to protect hands from refuse which may contain needles and glass.



Added surface to provide exeptional grip during application.



Designed to protect hands from direct contact with sharp edges such as glass, metal, ceramics and other materials.



Chemical resistant gloves for reducing the exposure of our hands to hazardous materials.



Glove is made from heavier material for greater wear and tear.



Designed for use where vibration can cause extreme and permanent damage to the hands.




Offers extra insulation protection against cold objects.



Protective impact resistant gloves protect effectively the palms and wrists against traumatic impacts.



Designed to protect the hand against sharp objects piercing the glove.





Used for inspection lines, can be made from lint-free material for less contamination.

Glove Sizina

No two hands are alike. Finger length relative to palm size is not constant from person to person. Additionally what constitutes a comfortable fit can vary considerably between individuals. Using one of the methods below will help you to find an approximate glove size, but no method of measurement can substitute for actually trying them on.

Glove Sizing

Place you right hand as shown, with your index finger against the black line. The measurement that follows the right side of your hand is your approximate glove size. This is a general guide only.

Using a Tape Measure and the Sizing Guide

Wrap a tape measure around your hand at the widest point (usually the knuckles) and make a loose fist. Note that measurement, round it to the nearest inch and refer to the chart below to find your approximate glove size.

Glove Size Measurement X-Small 6 Small 8 Medium 9 Large 10 X-Large XX-Large 11 12 XXX-Large **Glove Size** XS S M XL XXL $|\mathsf{XXXL}|$ Sizing Gauge

Minimal Risk - General Handling Gloves

The gloves in this section are for general every day use and there is minimal or no risk to the user. Gloves with this designation offer protection against light cuts, contusions, abrasions and mild detergents. Suitable for areas of 'minimal risk' where the effects on



hands without gloves would be easily reversible or superficial. These products are unmarked and self-certified.

Mixed Fibre **Gloves**

Knitted wrists with a fleece lining. Multi-purpose gloves for lightweight handling.



Mixed Fibre Gloves



	Only		
Size	Weight per 12	Order Code TFF-961	Price/Pr RND
9	1.10kg	-1050K	4.00
8	1.10kg	-1055K	4.00

Cotton Micro-dot Gloves

100% cotton gloves with micro-dot covered palm, thumb and forefinger.



Stockinette Gloves

Natural Colour

100% cotton. Knitted wrists. Multi-purpose gloves for lightweight handling.



Size Weight Order Code Price/Pr per 12 TFF-961 RND	((For Minimal Risk Only			
	Size	Weight per 12			
9 3.0kg -1020K 3.20	9	3.0kg	-1020K	3.20	

Stockinette Gloves

Bleached White

100% cotton. Knitted wrists. Multi-purpose gloves for lightweight handling.



CE	Minimal Risk Only			
Size	Weight per 12	Order Code TFF-961	Price/Pr RND	
7		-1010K	9.10	
9	2.60kg	-1000K	9.10	

Cotton Gloves

100% jersey cotton. Knitted wrists and fleece-lined. Multi-purpose gloves for lightweight handling.



CE	Risk Only		
Size	Weight per 12	Order Code TFF-961	Price/Pr RND
9	740g	-1045K	12.80



Cotton-Backed Leather Gloves







Cotton-Backed Leather Gloves

Leather palms, cotton backs and knitted wrists. For general handling.



740g -1160K 12.50 10

Terry Towelling Gloves Thick close loop pile gloves which cushion and protect,



Order Code

TFF-961

-1080K

31.90

Size

10

32oz

Terry Towelling Gauntlets

Thick close terry-towelling loop pile gloves which cushion and protect, also giving good insulation against heat or cold.





Size Weight Order Code Price/Pr			Risk Only	7	
per 10 TFF-961 RND		leight er 10	Wei per	Size	
10 32oz -1095K 16.20	40	32oz	32	10	





TFF-961

-9002B

Order Code

SSF-961

-1170K

Size

9

Number

PPP-2G

Price/Pr

RND

10.00

79.70

SEAMLESS

LATEX







Tuffgrip

General-purpose seamless cotton glove, with a natural latex palm coating to give excellent grip in

both wet and dry conditions. For use in warehouses, construction and refuse collection etc.

Medium-duty giving good puncture and abrasion resistance.



•,	The state of the s	
Size	Order Code TFF-961	Price/Pr RND
8	-6011B	25.10
9	-6012C	25.10
10	-6013D	25.10

Polka-Dot Gloves

Cotton backed gloves, with palms and fingers covered with vinyl dots to give high grip.

Knitted wrists.



Only			
Material Weight	Weight per 12	Order Code TFF-961	Price/Pr RND
6oz	0.80kg	-1250K	6.70
8oz	0.95kg	-1260K	6.70
10oz	1.00kg	-1280K	6.70



Goat Skin Nappa Gloves

Full grain goat skin gloves provide the highest degree of comfort, flexibility, as well as abrasion resistance. With a cotton stockinette back and velcro fastening to help ensure a good fit the gloves conform to your hands for optimum comfort and dexterity.



Size	Order Code TFF-961	Price/Pr RND
7	-4800A	41.80
8	-4801B	41.80
9	-4802C	41.80
10	-4803D	41.80

Hot Mill Gloves

Canvas fleece double palms, forefinger and thumb, with cotton drill back, knuckles and cuff. Good protection against heat.





Risk			
Size	Order Code TFF-961	Price/Pr RND	1
9	-1130K	10.00	ALCOHOL:

Polka-Dot Gloves

Cotton drill backed with polka-dot coated cotton palm, thumb and forefinger. Knitted wrist.



TFF-961

-1121K

-1100K

1110K

1120K

850g

RND

Foam Insulated Gloves

Fluorescent PVC coated foam insulated gloves with jersey lining and knitted wrists.



Cotton Drill Gloves

Standard

PROTECTION

PERSONAL

100% cotton drill. Knitted wrists. For lightweight and medium handling.

Size: 9.

For Minimal

	sk 1ly	
Colour	Material Weight	Weight per 12
Navy Blue	6oz	740g
Natural	6oz 7oz	740g 800g






7)	Risk Only		
Size	Weight per 10	Order Code TFF-961	Price/Pr RND
10	910g	-1540K	62.10




One-piece chrome leather palms with protection on finger tips and knuckles. Cotton backs.





7)	Risk Only		17121110
Size	Weight per 12	Order Code TFF-961	Price/Pr RND
10	1.60kg	-1300K	17.80



Heavy Duty Riggers

Reinforced with extra palm, index finger and thumb protection. Selected split leather palms, knuckles and finger



(€	For Minimal Risk Only		FLEECE LINED	PALMS
Size	Weig per	ght 12	Order Code TFF-961	Price/Pr RND
10	2.00)kg	-1320K	20.30



Standard **Chrome Riggers**

Chrome leather palms with protection on finger tips and knuckles. Cotton backs.



		1	
CE	For Minimal Risk	NYLON LINE	PALM
	Only		
Size	Weigh per 12	t Order Code SSF-961	Price/Pr RND
10	1 601/	4 1270K	16.00



Contractor

Superior Riggers

Selected split leather palms, knuckles and finger tips. Fleece-lined palm, cotton drill back. 2" reinforced safety cuffs with arterial protection.



C Minimal Risk Only	FLEECE LINED		
Colour	Weight	Order Code	Price

Colour	Weight per 12	Order Code TFF-961	Price/Pr RND
Red/White	2.70kg	-1360K	20.30
Blue/Gold	3.00kg	-1380K	21.40



Extra Grip Riggers

Maxidot® Standard

Two-piece chrome leather palms with protection on finger tips and knuckles. Cotton backs. 2" safety cuffs with arterial protection patches. Stitched and gathered elasticated backs.



Size: 9.



CCN	For linimal	EXTRA STR	RONG
7	Risk Only	FLEECE LINED	PALMS
Grade	Weight	Order Code	Price/P

Standard 2.60kg -1800K 21.80



Cold Resistant Riggers

Selected split leather palms, knuckles and finger tips. Cotton drill backs, 2" reinforced safety cuffs with arterial protection. Thinsulate® lined with a knitted wrist for extra



	ϵ	For Minimal Risk	THINSULATE	® LINED
	Size	Only Weight per 10	Order Code TFF-961	Price/Pr RND
ı	9	4 20kg	-1900K	69 70



Pigsplit Leather Riggers

High quality pig grain leather. Heavyweight elasticated cotton drill backing. Palm, thumb, forefinger, fingertip and knuckle



-	Only		
Size	Weight per 12	Order Code TFF-961	Price/Pr RND
10	1.90kg	-1315K	22.40

Cowhide Riggers

Cowhide leather palms with protection on finger tips and knuckles. Nylon lined palms, cotton backs. 2" cuffs with



CE	Minimal Risk Only		HARD WEA FLEECE LI	
Size	Weig per 1	tht 12	Order Code TFF-961	Price/Pr RND
10	3.00	kg	-1290K	45.20



Split Leather Riggers

Leather palms, fleece lined with protection on finger tips and knuckles. 2" cuffs with arterial protection patches.



CE	For Minimal Risk Only		FLEECE LINE	D PALM
Size	Weig per	ght 12	Order Code TFF-961	Price/Pr RND
10	1.90	Okg	-1310K	18.90



Knitted Wrist Riggers

Selected split leather palms with protection on finger tips, knuckles and index finger. Cotton backs and knitted wrists.



l		Only		
	Size	Weight per 12	Order Code TFF-961	Price/Pr RND
	10		-1370K	19.20

Nappa Palm Riggers

Nappa leather palm, knuckles and finger tips. 2" cuff with arterial protection patches.



	Only		FLE	ECE LIF	NED	
Colour		eight er 12	Order C		Price/Pr RND	
Multi Single		70kg 60kg	-133 -134		12.20 14.60	



Open Cuff Chrome Leather Gloves

With 2" open cuffs, easily removed. For general handling. Double palms for heavier use.





Cowhide Driver's Gloves

Elasticated back. Lined or unlined. Men's size.



Only			
Size	Weight	Order Code	Price/Pr
	per 12	TFF-961	RND
10 - Unlined	1.70kg	-1355K	48.20
10 - Lined	1.70kg	-1358K	52.30

Leather Driver's Gloves

Two-piece all-leather glove. Fleece lined. One-piece back. Elasticated cuff with velcro wrist adjustment.



CE	For Minimal Risk Only			_
Size	Weigh per 12	t Order Code TFF-961	Price/Pr RND	
10	2.50kg	-1670K	131.30	

Lined Gauntlet with Reinforced Thumb

Selected split leather one-piece backs. Fully lined, two-piece fleece hand and cotton cuff. Reinforced thumb and forefinger webbing.



Only		
Size	Order Code TFF-961	Price/Pr RND
10	-1960K	45.20



Vinyl Impregnated Gloves

Abrasion, oil, grease and water resistant. Economical alternative to light duty leather work



CE	Minimal Risk Only		
Size	Weight per 12	Order Code TFF-961	Price/Pr RND
10	3kg	-1990K	6.40



Lined Gauntlets

Selected split leather one-piece backs. Fully lined, two-piece lining, fleece hand and cotton cuff.

Size: 11.



CE	For Minimal Risk Only		
Colour	Weight	Order Code	Price/Pr
	per 10	TFF-961	RND
Green	3.10kg	-1600K	40.60
Red	3.10kg	-1620K	40.60



Fully Lined Gauntlets

Split leather one-piece backs. Fully lined, two-piece lining, fleece hand and cotton cuff.



ט	Risk Only		
Colour	Weight per Pair	Order Code SSF-961	Price/Pr RND
Green	250g	-1610K	51.70
Red	250g	-1620K	51.70



HAND PROTECTION - CAT II - ABRASION RESISTANT

Abrasion Resistant Gloves

Mechanical hazards are associated with handling rough or sharp objects that could damage skin such as brick, concrete, glass, and sheet metal. Mechanical hazards are not associated with moving machinery. Gloves can be a hazard if there is a possibility they could snag in moving parts and put the user in danger.



a) Abrasion resistance.

Scale 1 (low) to 4 (high). Cut resistance. Scale 1 (low) to 5 (high).

Tear resistance. Scale 1 (low) to 4 (high). d) Puncture resistance. Scale 1 (low) to 4 (high).

0 = Fail. X = No test carried out.

Each Abrasion Resistant glove in this section has a rating the higher the number, the greater the protection.



Price/Pr

RND

15.20

15.20

15.20









	Price/Pr RND	Order Code TFF-961	Size
•	7.30	-6330L	6
	7.30	-6331M	7
400	7.30	-6332N	8
	7.30	-6333P	9
. L	7.30	-6334Q	10

With cotton interlock liner. Combines the comfort of

surface, durable and washable. Ideal for assembly,

cotton with the protection of nitrile. Textured

Nitrile-Coated Gloves

fabrication and handling.

Open Backed Knitted Wrist Open backed to keep hands cooler in warm conditions.



Knitted Wrist Rigger with Spandex Back

Weight per 12

1.2kg

1.2kg

1.2kg

Fully PVC-Coated Gloves

Provide excellent dry grip for

general applications.

 \mathbf{C}_{i}

EN388

Size

Tough flexible PVC-coated gloves with knitted wrists.

High stretch Spandex backed knitted wrist rigger, designed to be comfortable to wear over extended periods and manufactured from the toughest and hardest wearing selected shoulder split leather with a heavyweight spandex


Order Code

TFF-961

-1390K

-1400K





L11366 4.1.3.2		
Size	Order Code TFF-961	Price/Pr RND
10	-1170K	37.70

LIGHTWEIGHT

Size	Colour	Order Code TFF-961	Price/Pr RND
8		-3540K	11.30
9	Yellow	-3560K	11.30
10		-3580K	11.30





-3740K

-3760K -3780K




14.00 14.00

14.00

Seamless Gloves

White polyurethane coating on a 13 gauge seamless knitted white nylon liner with knitted elasticated

cuffs. Polyurethane coating to palms and fingertips, provides dexterity and strong abrasion resistance for the handling of fine and dirty objects.





	Size	Colour	TFF-961	RND	Size	Colour	TFF-961	RND
l	6		-6310A	7.30	6		-6320A	7.30
ı	7	White	-6311B	7.30	7	Grey	-6321B	7.30
ı	8		-6312C	7.30	8	-	-6322C	7.30
ı	9	White	-6313D	7.30	9		-6323D	7.30
ı	10	wille	-6314E	7.30	10	Grey	-6324E	7.30
l					_11		-6325F	7.30

8

1.10kg

1.20kg









GROUP

961

For excellent resistance to abrasion, cuts and snags, punctures, grease and oil. Tough general-purpose gloves. 'Nitron' general-purpose. **CE** Intermediate design.

Manufactured from superior selected shoulder split leather with a green 8oz cotton drill back and 70mm rubberised cuffs for arterial protection. They are abrasion, cut and puncture resistant and the palm is fleece lined for your









Price/Pr Order Code Size TFF-961 RND 9 -2760K 14.90 10 -2780K 14.90

Open Back Knitted Wrist To keep hands cooler in warm conditions.

With extra wrist protection.









Order Code RTL-961

-7500K

<u></u>


Size

10

Manufactured from superior selected shoulder split leather and have a red 8oz cotton drill back and 70mm rubberised cuffs for arterial protection. They are abrasion, cut and puncture resistant and the palm is fleece lined















EN388 4.2.2.1	111	
Size	Order Code TFF-961	Price/P RND
10	-2800K	16.80





Price/Pr RND

30.70



Size	Order Code KEN-961	Price/Pr RND
10	-7500K	26.70

HAND PROTECTION - CAT II - TEAR RESISTANT

Tear Resistant Gloves

Mechanical hazards are associated with handling rough or sharp objects that could damage skin such as brick, concrete, glass, and sheet metal. Mechanical hazards are not associated with moving machinery. Gloves can be a hazard if there is a possibility they could snag in moving parts and put the user in danger.



a) Abrasion resistance. b) Cut resistance.

Scale 1 (low) to 4 (high). Scale 1 (low) to 5 (high). Each Tear Resistant glove in this section has a rating the higher the number, the greater the protection.

c) Tear resistance. d) Puncture resistance.

Scale 1 (low) to 4 (high). Scale 1 (low) to 4 (high).

0 = Fail. X = No test carried out.









Natural Rubber Seamless Gloves -Kevlar Lined

Premium quality blue natural rubber coating on a seamless **100% Kevlar® liner**, provides excellent wet and dry grip whilst offering outstanding blade cut resistance and protection from mechanical hazards. Raised latex crinkle finish coating to palms and fingertips, breathable open back and continuous knitted wrist.



Seamless Knitted Gloves

Tufflite™

Grey nitrile foam coating on a 13 gauge seamless knitted white nylon liner with knitted elasticated cuffs. Nitrile coating to palms and fingertips, provides excellent dexterity with precise grip.



Size	Order Code TFF-961	Price/Pr RND
6	-6300A	11.30
7	-6301B	11.30
8	-6302C	11.30
9	-6303D	11.30
10	-6304E	11.30



LATEX



Size	Order Code TFF-961	Price/Pr RND
8	-6111B	73.20
9	-6112C	73.20
10	-6113D	73.20



Knitted Cotton Gloves

Super-Grip™ Criss-Cross

Heavyweight knitted cotton gloves with high grip PVC lattice and elasticated wrists.



€ EN388	3.1.4.3	CAT II			
Size	Wei per		Order Code TFF-961	Price/Pr RND	
10	1.2	0kg	-1240K	11.30	


Latex-Coated Gloves

Tuffgrip II™

The Tuffsafe® coated latex gloves have a premium quality green natural rubber coating applied to a seamless polycotton liner to produce a glove with excellent wet and dry grip, whilst at the same time offering outstanding protection from mechanical hazards. Raised latex crinkle finish coating to







Size	Order Code TFF-961	Price/Pr RND
8	-5991B	11.00
9	-5992C	11.00
10	-5993D	11.00



Puncture Resistant Gloves

Many types of operator are exposed to sharp object injuries that can be caused by wooden or metal splinters and protruding nails and fixings in timbers, packing cases etc, that are often not clearly visible.



Abrasion resistance.

Scale 1 (low) to 4 (high).

Cut resistance. Tear resistance. Scale 1 (low) to 5 (high). Scale 1 (low) to 4 (high).

Puncture resistance. Scale 1 (low) to 4 (high). 0 = Fail. X = No test carried out.

Each Puncture Resistant glove in this section has a rating the higher the number, the greater the protection.



Reversible Welder's





İ	Natural Kevlar I	Rubber ined	Seamless	Gloves -


Tuffgrip KL™

Premium blue natural rubber coating on a seamless 100% **Kevlar® liner**, provides excellent wet/dry grip, cut resistance and protection from mechanical hazards. Raised latex crinkle



Size	Order Code TFF-961	Price/Pr RND
8	-6111B	73.20
9	-6112C	73.20
10	-6113D	73.20







with a green 8oz cotton drill back and 70mm rubberised cuffs for arterial protection. They are abrasion, cut and puncture resistant and the palm is fleece lined for your comfort. CE approved to






Size	Order Code RTL-961	Price/Pr RND	
10	-7500K	30.70	









Canadian Rigger Gloves

ExtraGrip™ Manufactured from superior selected shoulder split leather and have a red 8oz cotton drill back and 70mm rubberised cuffs for arterial protection. They are abrasion, cut and

puncture resistant and the palm is fleece lined for your comfort CE approved to BS EN 388 Cat II.



Size	Order Code KEN-961	Price/Pr RND
10	-7500K	26.70

















10

Gauntlet Reversible (ambidextrous) lined, green gauntlet. Type A. **CE** approved to EN12477, EN388, EN407. Price/Pr Weight Order Code Size KEN-961 RND per pair 10.5 250g -1940K 96.90



Full five finger welder's gauntlet manufactured from select split leather with a full cotton lining with a one piece back. Reinforced palm and thumb for increased wear with no exposed seams to burn. Kevlar® sewn throughout. Tested to



Size	Weight per Pair	Order Code TFF-961	Price/Pr RND
10	341g	-1580K	63.70

Grey Leather Tig Welder's Gloves Constructed from soft high quality nappa leather for the palm, and stiff 150mm chrome leather cuff. The soft leather palm and fingers offer a superb feel and good durability for precision welding. Good comfort and flexible with a good level of dexterity.






-1650K














For Minimal Risk	Size	Weight per box	Order Code Blue	TFF-961 Clear	Price/Pk RND
Only	61/2	0.80kg	-7010A	-7020A	52.80
л и о	71/2	0.89kg	-7011B	-7021B	52.80
	81/2	1.25kg	-7012C	-7022C	52.80
$-\iota - \iota - \iota$	91/2	1.35kg	-7013D	-7023D	52.80

Latex Disposable Gloves

-3123D

Micro textured natural rubber latex disposable gloves. Finger hugging latex provides maximum dexterity, sensitivity





91.90

PACK OF

10

-3113D

121.50



Powdered: For use in medical, veterinary laboratory and food processing conditions. Powdering on inside for ease of donning and perspiration absorption.

Non powdered: For use in electronics, pharmaceutical, laboratory, medical, dental and food processing applications.

Size	Type	Order Code TFF-961	Price/Pk RND	Size	Type	Order Code TFF-961	Price/Pk RND
6½ 7½ 8½ 9½	Powdered	-4020A -4021B -4022C -4023D	90.00 90.00 90.00 90.00	6½ 8½ 8½ 9½	Powder Free	-4010A -4011B -4012C -4013D	94.50 94.50 94.50 94.50

Back Support TUFFSAFE !

Provides comfortable support from lower back strain. Helps to reduce lower back discomfort. 8" wide elasticated double back support belt.









Front		васк	
	Waist Size	Order Code TFF-962	Price/Pr RND
	Small 28-32"	-2010A	394.60
	Medium 32-38"	-2011B	394.60
	Large 38-47"	-2012C	394.60
	X-Large 46-56"	-2013D	394.60

1¹/₄" wide adjustable shoulder straps.



One Strap Knee Pads

Chrome leather with one strap.



Size	Weight each	Order Code	Price/Pr
(mm)		KEN-962	RND
1200 Dia	220ø	-4960K	281.80

Moulded Rubber **Knee Pads**

Heavy duty. One piece construction. Manufactured from black polyurethane foam. Deep ribbed contact zone to reduce the risk of slipping. Five point adjustable elasticated strap. Conforms to, and is stamped CE. Suitable for regular use, industrial and professional applications.



Size	Order Code	Price/Pr
(mm)	KEN-962	RND
135 x 155	-4930K	316.50

Black Leather Knee Pads

Heavy duty. A robust construction with buckle straps and a felt padding lining for added comfort.



-4940K

160 x 130

396.80

Heavy Duty Knee Pads

Heavy duty chrome leather with two straps.



Size	Weight each	Order Code	Price/Pr
(mm)		KEN-962	RND
195 x 215	430g	-4920K	364.90

Neoprene Gel **Knee Pads**

Quick release velcro fastening. One size fits all. Flexible straps prevent binding behind the



Size	Order Code	Price/Pr
(mm)	KEN-962	RND
190 x 230	-5010K	274.20

Neoprene Gel **Elbow Pads**

Quick release velcro fastening. One size fits all. Flexible straps for added comfort. Gel filled pad absorbs impact.



Size	Order Code	Price/Pr
(mm)	KEN-962	RND
150 x 190	-5020K	130.30

High Density Foam Knee Pads

Quick release velcro fastening. One size fits all. Flexible straps prevent binding behind the knee. Non-marring face protects surfaces. Non-skid material helps avoid slipping. Lightweight design for comfort when standing.



Partial Hard Case Knee Pads

Quick release velcro fastening. One size fits all. Flexible straps prevent binding behind the knee. Non-marring face protects surfaces. Foam cushion beneath cap absorbs impact.



Size	Weight	Order Code	Price/Pr
(mm)	each	KEN-962	RND
180 x 250	200g	-4990K	164.40

Full Hard Case Knee Pads

Quick release velcro fastening. One size fits all. Flexible straps prevent binding behind the knee. Non-skid material helps avoid slipping. Non marring face protects surfaces. Foam cushion beneath cap absorbs impact.



Size	Order Code	Price/Pr
(mm)	KEN-962	RND
185 x 235	-5000K	342.30

Page **813**

Fall Arrest Equipment

Health and safety legislation states that fall protection measures must be put in place for any person working at a height of two metres or more where a fall hazard exists.

If it is not feasible to eliminate the hazard using a collective system, then a personal protective equipment system must be selected and used, be it a restraint, work positioning or fall arrest product.

This system consists of a full body harness, an intermediate attachment and an anchorage connector.

The systems can only be used if a suitable anchorage point is located close to the area.



Rope or Webbing Lanyards

The choice is primarily one of preference as they both offer the same high level of performance.

Rope Lanyards - Can become rigid and difficult to handle when dirty - but offer great durability and a longer working life than webbing.

Webbing Lanyards - Are more lightweight, visible and easier to handle than rope - but offer less durability.

Arrest Product Selection

Lanyards - Maximum length two metres. For work requiring limited movement.

Fall Arrest Blocks - 2.5 - 40m. Automatic retractable cable allows freedom of movement. For workers who need to move relatively quickly up and down on a worksite. The automatic braking system arrests a fall in seconds.

Rope Grabs - For freedom to move around an elevated worksite (this could be horizontal or vertical, fixed or flexible). In the event of a fall, the guided type fall arrester grabs onto the anchorage line and arrests the fall - resulting in limited travel.

Work at Height Regulations 2005

The Work at Height Regulations 2005 came into force on 6 April 2005. The Regulations apply to all work at height where there is a risk of a fall liable to cause personal injury.

They place duties on employers, the self-employed, and any person that controls the work of others (for example facilities managers or building owners who may contract others to work at

The Work at Height (Amendment) Regulations 2007 which came into force on 6 April 2007 apply to those who work at height providing instruction or leadership to one or more people engaged in caving or climbing by way of sport, recreation, team building or similar activities in Great Britain.

As part of the Regulations, duty holders must ensure:

- all work at height is properly planned and organised;
- those involved in work at height are competent;
- the risks from work at height are

- assessed and appropriate work equipment is selected and used;
- the risks from fragile surfaces are properly inspected and maintained.

There is a simple hierarchy for managing and selecting equipment for work at height. Duty holders must:

- avoid work at height where they can;
- use work equipment or other measures to prevent falls where they cannot avoid working at height; and
- where they cannot eliminate the risk of a fall, use work equipment or other measures to minimise the distance and consequences of a fall should one occur.

The Regulations include schedules giving requirements for existing places of work and means of access for work at height, collective fall prevention (eg guardrails and working platforms), collective fall arrest (eg nets, airbags, etc), personal fall protection (eg work restraints, fall arrest and rope access) and ladders.

Lanvard

Retractable Energy Absorbing Lanvard Block

Retractable mini web block ideal for personal issue to operatives working at height. The unit is designed to be connected and worn directly on a fall arrest harness. Locks on with decelerating brake action in the event of a fall and recoils the lanyard when slack is introduced to reduce trip hazards in tight work spaces. Compact design, built in shock pack. Has a working length of 2.5m. Certified to: CE 0320, EN364, EN360.

Max fall arrest force: 6KN.

Size (L x W x D): 100 x 110 x 75mm.



Parking Loops

Parking loops are simple and easy to use. Prevents wear on harness straps. The clip is designed to fit onto the shoulder strap of the harness. Once fitted the karabiner is connected directly to the loop for safe stowage when not in use.

This stops the lanyard from trailing on the floor and causing a trip hazard.

Model Number	Weight each	Order Code TFF-962	Price/1 RND		
TSPI	10g	-3935E	30.10		

Trauma Suspension Straps

Trauma suspension straps are simple and easy to use and can fit all Tuffsafe harnesses. They allow the worker to stand up in their harness to ease the discomfort whilst suspended from a lanyard after a fall. Helps release the tension within the harness straps to relieve pressure on the groin which helps prevent loss of circulation to the legs and feet. Prior to use attach one pack to the outer side of each leg strap. In the event of a fall unzip the pouches to release the straps and thread the plain end through both chrome rings and back through only one and pull tight to form a loop approx shin height.

Stand up slowly on the straps and the discomfort will be relieved. Lightweight and unobstructive.



Model Number	Weight each	Order Code TFF-962	Price/1 RND
TSTSS	150g	-3977F	117.20

Body Harness -

One point full body harness made of strong 45mm wide polyester webbing. Lightweight

and durable therefore ideal for all day comfort and dependability. Adjustable thigh and chest straps with metal buckles and back anchorage dorsal D-ring attachment. Capable of supporting up to 310lb (22st/140.6kg).



6 0321 EN 361:2002

Number	Order Code SSF-962	RND
BHP010	-8010K	577.30

Body Harness 2 Point

Two point full body harness made of strong 45mm wide polyester webbing. Lightweight and durable therefore ideal for all day comfort

and dependability. Adjustable thigh and chest straps with metal buckles and back anchorage dorsal D-ring attachment. Two point anchor straps for extra harnessing support. Capable of supporting up to 310lb (22st/140.6kg).



Body Harness 2 Point -With Belt

BHP020

Two point full body harness made of strong 45mm wide polyester webbing.

-8020K

766.20

Adjustable thigh and chest straps with metal buckles and back anchorage dorsal Dring attachment. Two point anchor straps for extra harnessing support. Detachable belt harness including adjustable strap with metal buckles and two D-rings.

Two polyester/plastic 90mm D-rings and clip attachment at the rear. Capable of supporting up to 310lb (22st/140.6kg).

€ 0321

- LIV 301.2002	L14301.2002	
Model Number	Order Code SSF-962	Price/1 RND
BHP025	-8025K	1277.50

The TuffSafe range of fall arrest harnesses are lightweight, durable and manufactured from 45mm water repellent polyester webbing with rip stitch fall indicators. Ideal for all day comfort and dependability. Fully adjustable for easy fitting. All fittings are made from high tensile steel

All TuffSafe harnesses are certified to: CE 0320, EN361, EN358, EN364.

Rear 'D' Harness

One point attachment: One dorsal D-ring.

Weight: 0.95kg.



Model	Harness	Order Code	Price/1
Number	Points	TFF-962	RND
TSH1	1	-3911A	465.20

Front & Rear 'D' Harness

Two point attachment:

One dorsal D-ring. One chest mounted D-ring.

Weight: 1.15kg.



Model	Harness	Order Code	Price/1
Number	Points	TFF-962	RND
TSH2	2	-3912B	

Front & Rear 'D' Harness

TSH3 Three point attachment: One Dorsal D-ring. Two side D-rings.



Model	Harness	Order Code TFF-962	Price/1
Number	Points		RND
TSH3	3	-3913C	863.80

Front & Rear 'D' Harness

TSH4 Four point attachment:

One dorsal D-ring. One chest mounted D-ring. Two side D-rings.

Weight: 1.75kg.



Model	Harness	Order Code TFF-962	Price/1
Number	Points		RND
TSH4	4	-3914D	1229.30

Shock Absorbers

Lightweight, durable and fitted with a shock absorber pack and a 70mm delta link. Certified to: CE 0320, EN 364, EN 355.

Max fall arrest force: 6KN.

TSSA1 & TSSA11

'Soft Edge' 32mm wide, cut resistant polyester webbing provides greater strength and resistance along with its water repellent coating can help prolong its life.



Model Number	Weight each	Order Code TFF-962	Price/1 RND
TSSA1	0.60kg	-3951B	453.90
TSSA11	0.90kg	-3961L	686.40

TSSA9

Twin legs allow movement between anchorage points. The elasticated lanyard reduces the amount of hanging slack. Lightweight, durable and fitted with a shock absorber pack and a 70mm delta link. The 35mm tubular webbing and tear webbing provides greater strength and resistance.



Model Number	Weight each	Order Code TFF-962	Price/1 RND
TSSA9	1.50kg	-3959J	1062.60

Page **815**

Disposable Coveralls

100% polypropylene single-use disposable coverall for minimal risk and nuisance. Provides protection from non-hazardous dust and liquid splash. Designed for comfortable fit with elasticated ankles, cuffs, hood and waist. Suitable for DIY and home maintenance, food processing, general cleaning, site visitors, stores and warehouse use etc.

TUFFSAFE†

'Guard Master' Disposable **Hooded Coveralls**

Type 5/6 coveralls. Disposable coveralls with hood, elastic cuffs, back and ankles. 1-way zip at front with 1-ply stormflap. Made from 55gsm SMS (spunbond, microporous spunbond) material with inside stitching. For noxious dust and splash. Ideal for dry particulate barrier and repellency. Lightweight and breathable. Liquid repellent. Designed to zip over neck to above the chin to protect exposed neck areas. EN13034 for limited protection against liquid particles (Type 6). EN13982-1 (Type 5) for protection against solid particles.

'Guard Master PLUS' Disposable **Hooded Coveralls**

Type 5/6 coveralls. Non-woven disposable coveralls with elasticated hood, cuffs, back and ankles. Antistatic. Liquid repellent. Diamond crotch gusset improves manoeuvrability. 2-way zip at front with 1-ply adhesive tape stormflap. Laminated microporous film 65gsm with inside stitching. Provides protection against airborne solid particulates, liquid chemicals, infective agents, chemical and radioactive contamination. Designed to zip over neck to above the chin to protect exposed neck areas. EN13982-1 (Type 5) for protection against solid particles.

EN1149-5 electrostatic properties. EN141126 for protection against infective

EN1073-2 for protection against radioactive contamination. EN13034/05 for limited protection against liquid





Overshoes supplied separately. Price/1 RND Order Code SSF-962 Colour Size Μ -1250C 66.50 -1250D 66.50 Blue XL -1250E 66.50 66.50 2XL -1250F M -1253C 66.50 66.50 -1253D L White

-1253E

-1253F

66.50

66.50

Order Code Price/1 Colour Size TFF-962 RNĎ -3800A 76.40 M -3801B 76.40 Blue -3802C 76.40 XL -3803D 76.40 3804E 76.40 76.40 -3810A -3811B 76.40 Μ -3812C 76.40 White ΧĹ -3813D 76.40 -3814E 76.40

0302



ΧĹ

Chrome Leather Welder's Clothing

A range of economically priced rugged workwear manufactured from high quality selected chrome leather. Spatter-resistant and tear-resistant. The full range offers head-to-toe protection against weld spatter and grinding sparks. Suitable for use in workshops, foundries and on-site.

Aprons

Generous fit for full torso and upper leg protection against weld spatter and grinding sparks, whilst offering freedom of movement for the wearer. All seams have heavy duty stitching for durability and extended wear. Available in a choice of tie or buckle

CE approved to EN470-1 CAT II.

Colours: available in a choice

of grey or red.



	Colour	W x L (cm)	Order Code KEN-885	Price/1 RND
Ī		Tie	Fastening	
Ī	Grey	60 x 90	-8020K	122.50
	Grey	60 x 105	-8030K	139.10
	Red	60 x 90	-5410K	130.80
Ī		Buck	le Fastening	
	Grey	60 x 90	-8060K	137.00
	Red	60 x 90	-5440K	141.20

Welder's Caps

Comfortable, durable and washable welder's caps. Double stitched construction with absorbent cotton sweat band. Can be worn with the peak to the rear when a screen is used. New improved version with taped, reinforced internal seams for extra durability and improved comfort.



Size	Weight each	Order Code WDA-957	Price/1 RND
71/8"	35g	-5500K	65.60
71/4"	35g	-5510K	65.60
73/8"	35g	-5520K	65.60
71/2"	35g	-5530K	65.60
75/8"	40g	-5540K	65.60
73/4"	40g	-5550K	65.60

For wearing over workshoes to protect against weld spatter and grinding sparks. With velcro fastening on back of calf and buckle adjustment around shoe. Double stitched and riveted seams for extra heavy duty use.


CE approved to EN470-1 CAT II.

Size: 35cm.



Sleeves

Can be used independently or in conjunction with an apron or other garment to offer optimum protection of the lower arm and elbow. With elasticated openings. All seams have heavy duty stitching for durability and extended wear. One size. CE approved to EN470-1 CAT II.



Stud fastening jacket for full neck to waist protection against weld spatter and grinding sparks. With external side pocket, neck is lined with soft split leather for extra comfort. All seams have heavy duty stitching for durability and extended wear.

CE approved to EN470-1 CAT II.



Colour	Size	Order Code KEN-885	Price/Pr RND
Grey	L	-8160K	467.00
Grey	XL	-8170K	467.00
Red	L	-5222K	467.00
Red	XL	-5223K	467.00





Disposable Visitor Coat

This single use SiteSafe® visitors coat is manufactured from low density polyethylene (LDPE) material and has front press stud fastening. One size only.



White	25	-9000K	

SSF-962

Quantity

Non-Woven Visitor Coats

This visitor's coat from Sitesafe® is manufactured from a 35gm2 non-woven material, it has a collar and a stud fastening front.

PACK OF

Colour



Order Code SSF-962 Price/Pk Pack Size Quantity RŃD -9002C 402.90 25 -9002D 402.90 -9002E 402.90

Polyethylene Oversleeves

Protective sleeve and arm covering, elasticated at both ends for a comfortable fit manufactured from polyethylene. Available in a range of colours. PACK OF

One size: 40 x 20cm (16" x 8").



Pack Quantity	Order Code SSF-962	Price/Pk RND
100	-5810B	59.90
100	-5810G	59.90
100	-5810R	59.90
100	-5810W	59.90
100	-5810Y	59.90
	Quantity 100 100 100 100	Quantity SSF-962 100 -5810B 100 -5810G 100 -5810R 100 -5810W

Disposable Overshoes

SiteSafe® overshoes provide cost effective solution to many of the problems associated with cross contamination that can be caused by dirty footwear. In many areas where a clean environment is important or required by regulation, staff and visitors are able to enter and move freely using their own footwear covered by a SiteSafe® overshoe.

Manufactured from polyethylene with an elasticated

closure.



249.20

Colour	Pack Quantity	Order Code SSF-962	Price/Pk RND
Blue	100	-5800B	59.90
Green	100	-5800G	59.90
Red	100	-5800R	59.90
White	100	-5800W	59.90
Yellow	100	-5800Y	59.90

Disposable Polythene Aprons

SiteSafe® disposable single use aprons manufactured from low density polythene. One size only 690 x 1070mm.



PACK OF

Colour	Pack Quantity	Order Code SSF-962	Price/Pk RND
Blue	100	-1150B	94.40
Green	100	-1150G	94.40
Red	100	-1150R	94.40
White	100	-1150W	94.40
Yellow	100	-1150Y	94.40

Disposable Hair Nets

Disposable bonded polypropylene hair nets have a fine open weave with stitched elasticated

opening. One size fits all.



			The second secon
Colour	Pack Quantity	Order Code SSF-962	Price/Pk RND
Blue White	100 100	-2900B -2900W	227.60 227.60

Bouffant Caps

The Sitesafe® disposable bouffant will completely cover your hair. Made from soft

and lightweight polypropylene with a stitched elasticised edge. One size fits all.



Colour	Pack Quantity	Order Code SSF-962	Price/Pk RND
Blue	100	-1260B	99.60
White	100	-1260W	99.60

Mob Caps

SiteSafe® Mob caps completely cover a person's hair. Manufactured from soft and comfortable, thermally bonded light polypropylene fibre with an encapsulated double stitched elasticated edge. One size fits all.





Colour		racn	Order Code	FIICE/FK
	Colour	Quantity	SSF-962	RŃD
	Blue	100	-5500B	86.30
	Green	100	-5500G	86.30
	Red	100	-5500R	86.30
	White	100	-5500W	86.30
	Yellow	100	-5500Y	86.30

Beard Masks

SiteSafe® with single elasticated fastening beard mask is manufactured from polypropylene. One size only.



Colour	Pack Quantity	Order Code SSF-962	Price/Pk RND
Blue	100	-1200B	83.00
White	100	-1200W	83.00

PACK OF

High Visibility Body Warmers

Certified to EN471 Class 2.



Size	Weight each	Order Code TFF-962	Price/1 RND
М	1050g	-4711B	184.30
L	1050g	-4712C	184.30
XL	1050g	-4713D	184.30
2XL	1050g	-4714E	184.30

Hi-Vis Polo Shirt

Two reflective bands around the torso and each sleeve, one band over each shoulder meeting **EN471 Class 3/2** requirements.



Size	Order Code TFF-962	Price/1 RND
М	-4731B	83.40
L	-4732C	83.40
XL	-4733D	83.40
2XL	-4734E	83.40

Hi-Vis Sweatshirt

Two reflective bands around the torso and each sleeve, one band over each shoulder meeting EN471 Class 3/2 requirements.





Size	Order Code TFF-962	Price/1 RND
M	-4741B	166.70
L	-4742C	166.70
XL	-4743D	166.70
2XL	-4744E	166.70

Lightweight Jackets

Satin yellow knitted polyester.

High Visibility Yellow All tape bands are 50mm wide.

BSEN471 1994: Class 3 area of fluorescent background and retro reflective tape.

BSEN471 1994: Class 2 retro reflective tape performance.



Available Sizes & Selection: Fit according to chest

size. A larger size may be required if worn over clothing.

	Sizing Guide		
	Size	Chest (cms)	Height
/	M	112-116	152-194
	L	116-120	152-194
	XL	120-124	152-194
	2XL	124-128	152-194

These garments of Directive requirements of Directive These garments comply with the 89/686/EEC and the above reference standards.

	nds Braces	Size	Weight each	Order Code TFF-962	Price/1 RND
2	✓	М	150g	-4411B	37.10
2	✓	L	200g	-4412C	37.10
2	✓	XL	300g	-4413D	37.10
2	✓	2XL	400g	-4414E	37.10

Hi-Vis Executive Vest

Two reflective bands around the torso and and one band over each shoulder meeting EN471 Class 2/2 requirements.

Lightweight and breathable vest. Zip front. External mobile phone pocket, pen pouch,



	The second second	
Size	Order Code TFF-962	Price/1 RND
М	-4721B	63.40
L	-4722C	63.40
XL	-4723D	63.40
281	-4724F	63 40

Hi-Vis Fleece Jacket

Two reflective bands around the torso and each sleeve, one band over each shoulder meeting **EN471 Class 3/2** requirements. Fleece comes with mesh inner lining, elasticated cuffs and two side entry pockets.



Size	Order Code TFF-962	Price/1 RND
М	-4751B	244.60
L	-4752C	244.60
XL	-4753D	244.60
2XL	-4754E	244.60

TUFFSAFE1 5-in-1 High Visibility Waterproof & Breathable Coats


A multi-function coat system for all seasons. An outer layer, detachable inner jacket, detachable inner sleeves and detachable hood giving multiple wear options to suit any weather conditions.

Outer Layer: Two reflective bands around the torso and each sleeve, one band over each shoulder meeting EN471 Class 3/3 requirements and EN343 Class 3/3. Two way zip with press stud storm flap protection. Fully taped seams. Fleece collar. External phone pocket and clear ID pouch. Two 'D' rings. Zip security pocket within the storm flap for easy access. Two external pockets with pop stud fastening plus two side slant pockets for easy access. Adjustable Velcro cuff straps. Inner layer retained by zips and

press studs. Zip access to shell for corporate identity/branding. Adjustable drawstring toggles on waist and hood.

Inner Layer/Body Warmer:

Two reflective bands around the torso, one band over each shoulder meeting **EN471 class 3/2** requirements. Dual purpose inner layer with reflective properties and inner quilted option when reversed. Fully taped seams. Two way zipper for attaching to outer layer or wearing independently. Fleece collar. External phone pocket with 'D' ring. Two external side pockets on both hi-viz and quilted layer. Elasticated cuffs. Removable zipped sleeves to create body warmer.



Size	Order Code TFF-962	Price/1 RND
S	-8010A	651.60
M	-8011B	651.60
L	-8012C	651.60
XL	-8013D	651.60
2XL	-8014E	651.60





Breathable **High Visibility Trousers**









215.60

1050g

Waterproof High Visibility Trousers

Satin yellow knitted polyester lightweight overtrousers with elasticated waist, velcro front fastening and fully taped waterproof seams. Complete with two 50mm reflective bands around each leg.

PREN343 1993:


Class 3 (highest) water penetration; Class 1 (lowest) water vapour resistance.

BSEN471 1994:

Class 1 area of fluorescent background and retro reflective tape.

BSEN471 1994: Class 2 retro reflective tape performance.

Yellow



These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Colour	Size	Weight each	Order Code TFF-962	Price/1 RND
	M	330g	-4021B	111.30
Yellow	L	350g	-4022C	111.30
Tellow	XL	360g	-4023D	111.30
	2XL	370g	-4024E	111.30
	M	330g	-4041B	111.30
Orongo	L	350g	-4042C	111.30
Orange	XL	360g	-4043D	111.30
	2XL	370g	-4044E	111.30





EN343 EN471



Available Sizes & Selection:

Fit according to waist size. This garment has a 20cm allowance built in for comfort and to allow the garment to be worn over light layers of clothing. If bulkier clothing has to be worn underneath, a larger size may be required.



Sizing Guide						
Size	Waist (ins)	Waist (cms)	Height			
M	32-34	80-84	170-176			
L	34-36	88-92	176-182			
XL	36-38	82-96	182-188			
2XL	40-42	100-104	188-194			

Waterproof High Visibility Jackets

Two hip pockets with velcro fastened flaps. Drawstring hood. Knitted storm cuffs. Two way zip front with studded storm flap. Inside pocket.

PREN343 1993:

Class 3 (highest) water penetration;

Class 1 (lowest) water vapour resistance.

BSEN471 1994:

Class 3 area of fluorescent background and retro reflective tape.

BSEN471 1994:

Class 2 retro reflective tape performance.

Available Sizes & **Selection:**

Fit according to chest size. This garment has a 20cm allowance built in for comfort and to allow the garment to be worn over light layers of clothing. If bulkier clothing has to be worn underneath, a larger size may be required.





Sizing Guide							
Size	Chest (ins)	Chest (cms)	Height				
М	37-39	92-100	170-176				
L	39-43	100-108	176-182				
XL	43-46	108-116	182-188				
2XL	46-49	116-124	188-194				

C These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Bands		Size	Weight	Order Code	Price/1
Body	Braces	Size	each	TFF-962	RND
2	✓	М	1.4kg	-4111B	267.40
2	✓	L	1.4kg	-4112C	267.40
2	✓	XL	1.4kg	-4113D	267.40
2	✓	2XL	1.4kg	-4114E	267.40

Waterproof High Visibility Coats

Satin yellow PU coated polyester with fixed nylon quilted lining. Two internal breast pockets, two exterior pockets with storm flaps and rear access for corporate identity logo heat attachment. Heavy weight two way zip with studded storm flap knitted storm cuffs, concealed hood with drawstring. Fully taped seams. All highway jackets have 2x 50mm sleeve bands. Uses 3M Scotchlite retro-reflective glass bead tape.

PREN343 1993:

Class 3 (highest) water penetration; Class 1 (lowest) water vapour resistance.

BSEN471 1994:

Class 3 area of fluorescent background and retro reflective tape.

BSEN471 1994:

Class 2 retro reflective tape performance.





Available Sizes & Selection:

Fit according to chest size. This garment has a 20cm allowance built in for comfort and to allow the garment to be worn over light layers of clothing. If bulkier clothing has to be worn underneath, a larger size may be required.

Sizing Guide

OIZING GUIGO			
Chest (ins)	Chest (cms)	Height	
37-39	92-100	170-176	
39-43	100-108	176-182	
43-46	108-116	182-188	
46-49	116-124	188-194	
	Chest (ins) 37-39 39-43 43-46	Chest (ins) Chest (cms) 37-39 92-100 39-43 100-108 43-46 108-116	





These garments comply with the requirements of Directive These garments comply with the requirements 89/686/EEC and the above reference standards.

Bands		Size	Weight	Order Code	Price/1
Body	Braces	Size	each	TFF-962	RNĎ
2	✓	M	0.9kg	-4011B	280.00
2	✓	L	1.0kg	-4012C	280.00
2	✓	XL	1.0kg	-4013D	280.00
2	✓	2XL	1.2kg	-4014E	280.00



These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Bands		Size	Weight	Order Code	Price/1
Body	Braces	Size	each	TFF-962	RND
2	✓	М	0.9kg	-4031B	298.90
2	✓	L	1.0kg	-4032C	298.90
2	✓	XL	1.0kg	-4033D	298.90
2	✓	2XL	1.2kg	-4034E	298.90

Manufactured to **BS EN 471** 100% polyester with velcro fastening. All tape bands are 50mm wide.

EN471



Sizing Guide:

Fit according to chest size. A larger size may be required if worn over clothing.

Garment Size	Chest Size - cm	Height cm
М	112-116	152-194
L	116-120	152-194
XL	120-124	152-194
XXL	124-128	152-194
XXXL	128-134	152-194

These garments comply with the requirements of Directive 89/686/EEC and the reference standards listed below.

CE

Breathable High Visibility Coats




Certified to EN471 Class 3.
Certified to EN343 Class 2 breathing fabric.
Polyester with PU coating. Concealed hood, full zip front with double storm flap.
Nylon/polyester quilt lining, self double yoke back.

Lower pockets with flap and elasticated storm cuffs. Stitched and welded seams. Reflective material.



Size	Weight each	Order Code TFF-962	Price/1 RND
М	1050g	-4051B	436.00
L	1050g	-4052C	436.00
XL	1050g	-4053D	436.00
2XL	1050g	-4054E	436.00

BS EN 471 Class 3 - Yellow 1 Body Band with Braces




2	Body	y Bands	with E	3rac	

BS EN 471 Class 2 - Yellow

EN 471		nds	Size	Weight	Order Code	Price/1
Class	Body	Braces	0.20	each	TFF-962	RND
			M	135g	-4211B	23.30
3	1	✓	L	150g	-4212C	23.30
3	_	•	XL	270g	-4213D	23.30
			2XL	350g	-4214E	23.30
			M	135g	-4231B	23.30
			L	150g	-4232C	23.30
2	2	✓	XL	270g	-4233D	23.30
			2XL	350g	-4234E	23.30
			3XL	350g	-4235F	23.30

BS EN 471 Class 3 - Orange 1 Body Band with Braces



BS EN 471 Class 2 - Orange

2 Body Bands with Braces

EN 471 Class	Body	ands Braces	Size	Weight each	Order Code TFF-962	Price/1 RND
3	1	✓	M L XL 2XL	135g 150g 270g 350g	-4241B -4242C -4243D -4244E	23.30 23.30 23.30 23.30
2	2	✓	M L XL 2XL 3XL	150g 270g 270g 350g 350g	-4251B -4252C -4253D -4254E -4255F	23.30 23.30 23.30 23.30 23.30

TUFFSAFE †

Cotton Drill Boiler Suits

Comfortable fit suitable for garage, workshop, service, maintenance, general DIY and many other applications. Hard wearing.
Concealed press studs. Chest pockets, side pockets, back pocket and lower leg pocket.
Elasticated waist. Machine washable.
Made from 100% cotton.

Colour: navy.

Polycotton Boiler Suits

Comfortable fit suitable for garage, workshop, service, maintenance, general DIY and many other applications. Hard wearing. Concealed press studs. Chest pockets, side pockets, back pocket and lower leg pocket. Elasticated waist. Easy care and higher wash rate due to the shrink resistant and colour fade resistant polycotton fabric. Machine washable. Made from 80% polyester, 20% cotton.

Colour: royal blue.



Colour	Size	Order Code TFF-962	Price/1 RND
Navy Blue	S 36/38" M 40/41"	-2510A -2511B	304.40 304.40
	L 42/44"	-2512C	304.40
	XL 46/48" 2XL 50"	-2513D -2514E	304.40 304.40

Colour	Size	Order Code TFF-962	Price/1 RND
Royal Blue	S 36/38" M 40/41" L 42/44" XL 46/48" 2XL 50"	-5810A -5811B -5812C -5813D -5814E	133.40 133.40 133.40 133.40 133.40

Waterproof Suits

Waterproof hooded jacket with drawstring closure, storm front with plastic zipper, raglan sleeves with wind cut off, patch pockets with flap in the front and vented cape back and underarm vents for improved user comfort. The trousers have elasticated waist band, no fly front and press stud ankle adjustment.



Colour Size Weight each Order Code TFF-962 Price/1 RND Green S 1.00kg -5010A 53.40 M 1.05kg -5011B 53.40 XL 1.10kg -5012C 53.40 XL 1.20kg -5013D 53.40 Orange M 1.05kg -5020A 53.40 XL 1.10kg -5021B 53.40 XL 1.20kg -5023D 53.40 Yellow M 1.05kg -5030A 53.40 Yellow M 1.05kg -5031B 53.40 XL 1.10kg -5032C 53.40 XL 1.20kg -5033C 53.40 XL 1.20kg -5033D 53.40					
Green M L 1.05kg L 1.10kg -5011B 53.40 53.40 XL 1.20kg -5013D 53.40 N 1.20kg -5013D 53.40 S 1.00kg -5020A 53.40 Orange L 1.10kg -5021B 53.40 XL 1.20kg -5022C 53.40 XL 1.20kg -5023D 53.40 Yellow M 1.05kg -5031B 53.40 L 1.10kg -5031B 53.40 L 1.10kg -5032C 53.40	Colour	Size			
L 1.10kg -5012C 53.40 XL 1.20kg -5013D 53.40 S 1.00kg -5020A 53.40 Orange M 1.05kg -5021B 53.40 XL 1.10kg -5022C 53.40 XL 1.20kg -5023D 53.40 Yellow M 1.05kg -5030A 53.40 L 1.10kg -5031B 53.40 1.10kg -5032C 53.40		S	1.00kg	-5010A	53.40
Orange M 1.05kg -5012C 53.40 NL 1.20kg -5013D 53.40 S 1.00kg -5020A 53.40 L 1.10kg -5021B 53.40 XL 1.20kg -5022C 53.40 XL 1.20kg -5023D 53.40 S 1.00kg -5030A 53.40 Yellow M 1.05kg -5031B 53.40 L 1.10kg -5032C 53.40	Green	M	1.05kg	-5011B	53.40
Orange S 1.00kg -5020A 53.40 L 1.10kg -5022C 53.40 XL 1.20kg -5023D 53.40 Yellow M 1.05kg -5030A 53.40 L 1.10kg -5030A 53.40 L 1.10kg -5031B 53.40 L 1.10kg -5032C 53.40	arcen	L	1.10kg	-5012C	53.40
Orange M L 1.05kg 1.10kg 7 -5021B -5022C 53.40 53.40 XL 1.20kg 1.20kg -5023D 53.40 S 1.00kg 1.05kg -5030A 53.40 Yellow M L 1.10kg -5031B 53.40 L 1.10kg -5032C 53.40		XL	1.20kg	-5013D	53.40
L 1.10kg -5022C 53.40		S	1.00kg	-5020A	53.40
Yellow L 1.10kg -5022C 53.40 XL 1.20kg -5023D 53.40 S 1.00kg -5030A 53.40 L 1.10kg -5031B 53.40 L 1.10kg -5032C 53.40	Orange	M	1.05kg	-5021B	53.40
Yellow S 1.00kg -5030A 53.40 M 1.05kg -5031B 53.40 L 1.10kg -5032C 53.40	Orange	L	1.10kg	-5022C	53.40
Yellow M 1.05kg -5031B 53.40 L 1.10kg -5032C 53.40		XL	1.20kg	-5023D	53.40
L 1.10kg - 5032C 53.40		S	1.00kg	-5030A	53.40
L 1.10kg -5032C 53.40	Yellow	M	1.05kg	-5031B	53.40
XL 1.20kg - 5033D 53.40		L	1.10kg	-5032C	53.40
		XL	1.20kg	-5033D	53.40

Trentino

Waterproof and abrasion-resistant winter jacket with waterproof zip. Two zipped front pockets and two zipped inside breast pockets.

Adjustable cuffs with 'Hook & Loop' fastening and elasticated drawstring waist. Foldaway drawstring hood concealed in the collar. 100% polyester lightweight Microfleece mesh lining with micro-knit body panels. PU coated. Durable Taslon outer fabric and inner insulating fibre. Zipped embroidery access to allow corporate identity to be added.



Colour	Size	Order Code TFF-962	Price/1 RND
	S	-8520A	410.90
	M	-8521B	410.90
Navy	L	-8522C	410.90
-	XL	-8523D	410.90
	2XL	-8524E	410.90

Soft Shell Jackets

Roma

Lightweight, waterproof and wind-resistant jacket with two zipped hip pockets and an outer zipped breast pocket with thru 'headphone' hole designed for use with personal stereos. Adjustable cuffs with 'Hook & Loop' fastening. Microfibre fleece lining and mesh lining. Elasticated drawstring inside waist. Zipped embroidery access to allow corporate identity to be added to breast area. 100% lightweight polyester.



Colour	Size	Order Code TFF-962	Price/1 RND
	S	-8000A	408.00
Black	M	-8001B	408.00
	L	-8002C	408.00
	XL	-8003D	408.00
	2XL	-8004E	408.00
	3XL	-8005F	408.00

Lined Microfleece Jackets

Soft Microfleece jacket made from microfibres that make it water-repellent and windresistant. Two vertically zipped side pockets and one outer breast pocket. Fully lined with elasticated cuffs. Elasticated drawstring waist.







Colou	r Size	Order Code TFF-962	Price/1 RND
	S (38")	-4900A	232.00
	M (40")	-4901B	232.00
Black	L (42"/44")	-4902C	232.00
DIACK	XL (46")	-4903D	232.00
	2XL (48")	-4904E	232.00
	3XL (50"/52")	-4905F	232.00
	S (38")	-4920A	232.00
Navy	M (40")	-4921B	232.00
	L (42"/44")	-4922C	232.00
	XL (46")	-4923D	232.00
	2XL (48")	-4924E	232.00
	3XL (50"/52")	-4925F	232.00

Tradesman Trousers

Milano

Heavyweight tradesman trousers with two hip pockets, two rear pockets and two internal kneepad pockets. Button fasten waistband with large belt loops and zip fly. Rear hanging loop. Double stitched seams and reinforced gusset. 300gsm heavyweight fabric. 65% polyester 35% cotton.





Colour	Size	Order Code TFF-962	Price/1 RND
	30"	-6000A	246.70
	32"	-6001B	246.70
Navy	34"	-6002C	246.70
31" Leg	36"	-6003D	246.70
_	38"	-6004E	246.70
	40"	-6005F	246.70
	30"	-6010A	246.70
	32"	-6011B	246.70
Navy	34"	-6012C	246.70
33" Leg	36"	-6013D	246.70
	38"	-6014E	246.70
	40"	-6015F	246.70

Premium Tradesman Jackets

Premium quality tradesman jacket with front and back reflective beading that runs from cuff to cuff. Two front pockets and two breast pockets with 'Hook & Loop' fastening. Chunky front zip with storm flap with 'Hook & Loop' and press stud fasteners. Concealed drawstring hood. Adjustable cuffs with 'Hook & Loop' fastening and elasticated drawstring waist. Zip out quilt lining.

Zipped embroidery access to allow corporate identity to be added. 300gsm heavyweight fabric. 65% polyester 35% cotton. Designed to co-ordinate with the Sicilia tradesman's trousers.



See Below for **Trouser Details**

Colour	Size	Order Code TFF-962	Price/1 RND
	S	-6100A	498.00
	M	-6101B	498.00
Grey/Black	L	-6102C	498.00
Gley/Black	XL	-6103D	498.00
	2XL	-6104E	498.00
	3XL	-6105F	498.00

Premium Tradesman Trousers

Sicilia

Premium quality, multi-pocket work trousers with 11 different size pockets including a mobile phone pocket. Double hook and bar fastening waistband with zip fly and belt loops. Stitched seams and reinforced gusset with extra stitching on stress areas. External kneepad pockets. 300gsm heavyweight fabric. 65% polyester 35% cotton.

Designed to co-ordinate with the Sicilia tradesman's jacket.

Colour: grey/black.

O 37			
Waist Size	Inside Leg	Order Code TFF-962	Price/1 RND
30"		-6140A	345.50
32"		-6141B	345.50
34"	31"	-6142C	345.50
36"	31	-6143D	345.50
38"		-6144E	345.50
40"		-6145F	345.50
30"		-6160A	345.50
32"		-6161B	345.50
34"	33"	-6162C	345.50
36"	33	-6163D	345.50
38"		-6164E	345.50
40"		-6165F	345 50

Lightweight Waterproof Jackets

Toscana

Lightweight, breathable and wind-resistant waterproof jacket with two front pockets and two inside breast pockets all with zips and storm flaps. Elasticated cuffs with adjustable 'Hook & Loop' fastening. Elasticated drawstring hem. Concealed hood with elasticated drawstring. Internal loop to retain ear phones. Manufactured from 100% polyester. 110gsm micro fibre. PU coated/Mesh lining. Zipped embroidery access to allow corporate identity to be added. Contrast logo area on rear neckline. Designed to co-ordinate with the Toscana lightweight waterproof trousers.



Order Code **TFF-962** Price/1 RND Colour Size -4820A 350.80 M L 4821R 350.80 350.80 Navv -4822C 350.80 350.80

Lightweight Waterproof Trousers

Lightweight, breathable and wind-resistant waterproof trousers with two front pockets and one back pocket all with zips and storm flaps. 1/3 length leg zips allow these trousers to be put on/removed whilst wearing boots. Elasticated waistband with belt loops. Zip fly with double press-stud fasteners. Manufactured from 100% polyester. 110gsm micro fibre. Fully lined. PU coated. Designed to co-ordinate with the Toscana lightweight waterproof jacket.

Colour	Size	Order Code TFF-962	Price/1 RND
	S	-4860A	258.70
	M	-4861B	258.70
Navy	L	-4862C	258.70
•	XL	-4863D	258.70
	2XL	-4864E	258.70



Firenze

Classic heavyweight polo shirt with three button placket and colour matched buttons. Double knit pique weave with taped shoulder and neck seams and ribbed collar and cuffs. 230gsm heavyweight fabric. 50% polyester 50% cotton.

Colours: white, navy, sky blue, royal blue, red, burgundy, green and black. Sizes range from small (37"/39") to 4XL (50"/52").





Black Burgundy





Royal

Sky Blue

Navy







80.30

Order Code TFF-962 Colour Price/1 RND Size **Black** Burgundy Green Navy Red Royal Blue Sky Blue White S (37"/39") M (40"/42") L (41"/43") XL (42"/44") 2XL (44"/46") 3XL (47"/49") 4XL(50"/52") -5520A -5560A -5600A -5620A 80.30 -5500A -5540A -5580A -5640A -5501B -5521B -5561B -5581B -5641B -5541B -5601B -5621B 80.30 -5622C -5623S 5502C -5522C -5542C -5562C -5582C -5602C 5642C 80.30 -5503D -5523D -5543D -5563D -5583D -5603D -5643D 80.30 -5544E -5545F -5504E -5524E -5564E -5584E -5604E -5624E -5644E 80.30 -5525F -5565F -5585F -5625F -5645F -5505F -5605F 80.30 -5626G -5646G -5506G -5526G -5546G -5606G

-5586G

-5566G



Short sleeve T-shirt made from 160gsm breathable polyester fabric and antistatic dry-fit material with Ciba® Wick Away treatment that removes moisture away from the body.


100% polyester.





lack V-Neck		
Size	Order Code TFF-962	Price/1 RND
S (36"/38")	-3600A	163.50
M (38"/40")	-3601B	163.50
L (40"/42")	-3602C	163.50
XL (43"/45")	-3603D	163.50
2XL (45"/47")	-3604E	163.50









Premium sweatshirt manufactured from 300gsm heavyweight fabric that has been treated for anti-pilling to help prevent bobbling. Elasticated wrists, waist and neckline. 65% polycotton, 35% cotton.

Available Sizes: (36"/38")(46"/48") (38"/40") (50"/52") XL 2XL (42"/44")

Other Colours:





Burgundy

Navy

Royal

Green





						$\overline{}$
		Orde	er Code TFF-96	62		
Size			Colour			Price/1
	Black	Burgundy	Green	Navy	Royal Blue	RNĎ
S (36"/38")	-7000A	-7010A	-7020A	-7030A	-7040A	119.70
M (38"/40")	-7001B	-7011B	-7021B	-7031B	-7041B	119.70
L (40"/42")	-7002C	-7012C	-7022C	-7032C	-7042C	119.70
XL (43"/45")	-7003D	-7013D	-7023D	-7033D	-7043D	119.70
2XL (45"/47")	-7004E	-7014E	-7024E	-7034E	-7044E	119.70

Fleece Jackets

Front zip which matches the body colour. Two slanting front pockets which have pocket liners that are securely tacked to the bottom hem. Self-elasticated bottom hem. Twin needle stitching at arm-hole seam. Long sleeves with self-elastication at cuffs. 100% polyester polar fleece. One side

anti-pilling (prevents bobbling). Colour: navy.



Colour	Size	Order Code KEN-962	Price/1 RND
	S	-7100K	385.30
Navy	M	-7110K	385.30
	L	-7120K	385.30
	XL	-7130K	385.30
	2XL	-7140K	385.30

Quarter Zip Shirts

San Marco

Quarter zip shirt manufactured from 160gsm breathable Polyester fabric and antistatic dry-fit material with Ciba® Wick-Away' treatment. 100% polyester. Ciba® Wick-Away' treatment removes

moisture away from the body.

Colour: black/charcoal.



Size	Order Code TFF-962	Price/1 RND
Bl	ack/Charcoal	
S (36"/38")	-3510A	277.80
M (38"/40")	-3511B	277.80
L (42"/44")	-3512C	277.80
XL (46"/48")	-3513D	277.80
2XL (50"/52")	-3514E	277.80

Checked Workshirt

Padded

and button cuffs.

100% cotton outer and lining with 100% polyester padding. Full button front fastening, two breast pockets with button flaps



Colour	Size	Order Code KEN-962	Price/1 RND
Green	1	-3920K	266 80

pot Protectio

The wearing of foot protection in hazardous areas is a requirement under regulation 4 of the Personal Protective Equipment at Work Regulations 1992. This regulation requires employees to provide suitable personal protective equipment to employees exposed to health and safety risks. Feet need to be protected from hazards such as wet, electrostatic build-up, slipping, cuts and punctures, falling objects, metal and chemical splash and abrasion.

Note: Footwear can have a variety of sole patterns and materials to prevent slips in different conditions, have oil or chemicalresistant soles, and be antistatic, electrically conductive or insulating. There are a variety of styles including 'trainers' and boots with ankle support.

Footwear Classification System - A Brief Guide

S Safety Basic to EN ISO 20345 200 Joules Toe Protection.

For Class S1 and SB with Steel Midsole S1P and SBP classification is used).

Anti-static and Energy Absorbing Heel.

Steel Midsole.

Water-Resistant Upper.

Safety Basic to EN ISO 20345 200 Joules Toe Protection. All rubber or all polymeric footwear with Antistatic and Energy Absorbing Heel.

Water-resistant Upper and Steel Midsole.



200 Joules steel toe cap impact protection. Guards against falling objects and collisions (unless stated).



Oil, petrol, water, acid and alkali resistant.



Water penetration and absorption resistant. Helps keep feet dry in wet conditions.



Steel midsole to prevent sharp object penetration. Ideally suited to building sites and where metal swarf is present on floors.



Resists the build-up and conductance of static electricity. Of most benefit when walking on synthetic carpets or near electrical machinery.



Lightweight. Normally polyurethane soles with breathable uppers. Reduces fatigue during extended wear.



Non-metallic protection Kevlar composite toe cap and sole plate. For working in areas where security screening is a necessity. 200 Joules impact protection (unless stated).



Dual density polyurethane/rubber soles for extra comfort. The sole features a nitrile rubber outsole, resistant to heat to 300° and a low density polyurethane interlayer, for increased comfort and shock absorption.



Specially shaped inner sole to support arches and toes.



Normally allows walking on hot surfaces up to 300°C (unless stated).



Wider fitting for extra comfort. Also allows the user to wear thick work

Most shoe companies do not use absolutely correct size conversions and so it is quite common to have some variation from these tables. The table represents the 'best fit' solution i.e. calibrated to the nearest size to it's counterpart.

Sizing Guide (Sizes are not standard)

UK	3	4	5	6	7	8	9	10	11	12	13
Continental	36	37	38	391/2	401/2	42	43	441/2	45 ¹ / ₂	47	48
Asia	22	23	24	25	26	27	28	29	30	31	32
USA (Men) (Women)	4 4½	5 5 ¹ / ₂	6 6½	7 7½	8 8½	9 9 ¹ / ₂	10 10½	11 11 ¹ / ₂	12 12 ¹ / ₂	13	14

Mid-Cut Safety Boots Steel Midsole

BWB 08


PERSONAL PROTECTION

Manufactured to EN345. Dual density, anti-static and energy absorbing heel. Water-resistant upper, waterproof and breathable lining with a steel midsole. 200 joules toe protection.

Colour: black.

Size	Order Code TFF-963	
6	-0806D	
7	-0807E	
- <u>8</u>	-0808F	
9	-0809G	
10	-0810H	
11	-0811J	
12	-0812K	
Price/Pair		





725.60

Rigger TUFFSAFE 🕈 Boots

Tuffsafe Rigger boots are a pull-on safety boot popular with tradesmen and construction workers, designed to cope with the demanding working conditions found in most outdoor on-site environments. Tuffsafe Rigger boots are the ideal safety footwear for winter weather as they go a third of the way up the leg this keeps your feet dry and the bottom of your trousers clean as you can tuck them in the top of the boot. Lined rigger boots are tough on the outside, soft and warm on the inside, they have been manufactured to provide comfort and safety when worn all day, in the most challenging weather conditions you'll encounter on-site.



Manufactured to EN ISO **20345:2011**. 200J steel toecap. Steel midsole. Anti-static dual density polyurethane/rubber sole. Water penetration and absorption resistant. Oil, petrol, water, acid and alkali resistant.

Colour: tan.

Size	Order Code TFF-963	
5	-1245C	
6	-1246D	
7	-1247E	
8	-1248F	
9	-1249G	
10	-1250H	
11	-1251J	
12	-1252K	
Price/Pair		


RŃD

262.30

6" Safety Boots

BAB 04 These leather safety boots from the Tuffsafe premier safety footwear range incorporate hard wearing dual density polyurethane anti-static soles for your comfort. They have steel midsoles and are heat-resistant to 200°C with 200 joules

NEW





Price/Pair RND 589.20

Size

11



Safety Wellingtons Black. Energy absorbing heel.

Tough construction. Manufactured to EN ISO 345.


Size	Order Code SSF-963
3	-2003K
4	-2004K
5	-2005K
6	-2006K
7	-2007K
8	-2008K
9	-2009K
10	-2010K
11	-2011K
12	-2012K
Pri	ice/Pair

RND 197.40



Lined Steel Midsole Rigger Boots

Manufactured to EN345. 200 joules steel toecap, steel midsole, antistatic dual density polyurethane/rubber sole, temperature-





Fur-lining.

Size	Order Code TFF-963
6	-0676D
7	-0677E
8	-0678F
9	-0679G
10	-0680H
11	-0681J
12	-0682K

Price/Pair RŃD 413.70

SIP



Rigger Boots

Black. Man-made fibre lined. Dual density anti-static sole. Steel midsole. Manufactured to EN345.

Energy absorbing heel. Water-resistant upper.

200 joules toe protection.




SAFETY FOOTWEAR

Nubuck Welted Safety Boots Steel Midsole

Manufactured to EN345. Goodyear welt construction. Ultra flexible and lightweight sole. Steel midsole. 200 joules toe protection.

Colour: honey.



Safety Boots

Steel toe and midsole chukka boot/shoe, split leather upper, antistatic properties, dual density PU/PU outsole, padded collar for extra support, padded tongue for extra comfort, lightweight and flexible, S1P specification, fully conforming to EN ISO 345 Standards.

Colour: black.



Welted Safety Boots Steel Midsole

SBP

Manufactured to EN345. Goodyear Welt construction. Ultra flexible and lightweight sole. Steel midsole.



Nubuck Hiker Safety Boots

BBH 03

Manufactured to EN345. Cemented construction, lightweight rubber sole. Heat resistant to 200°C.



Boots

SSF05

Manufactured to EN345. 200J steel toecap. Steel midsole. Oil, petrol, water acid and alkali resistant.





















TUFFSAFE† Safety Shoes Steel Midsole

SWB 07

Black. Manufactured to EN345. Anti-static and energy absorbing heel. Dual density polyurethane rubber sole. Waterresistant upper and steel midsole. Heat-resistant to 300°C. 200 joules toe protection.

Size	Order Code TFF-963
6	-0706D
7	-0707E
8	-0708F
9	-0709G
10	-0710H
11	-0711J
12	-0712K



Safety Ankle Boots

Using the latest materials such as Kevlar and composite technologies. PU and leather upper, EVA/RB outsole. Manufactured to EN ISO 345.

Size	Order Code TFF-963
6	-0150D
7	-0151E
8	-0152F
9	-0153G
10	-0154H
11	-0155J
	04 = 01/



Safety Trainers

Manufactured to EN ISO 345. Using the latest materials such as Kevlar and composite technologies. PU and leather upper, EVA/RB outsole.





Safety

Black. Steel toe and midsole chukka boot/shoe, split leather upper, anti-static properties, dual density PU/PU outsole, padded collar for extra support, padded tongue for extra comfort, lightweight and flexible, S1P specification, fully conforming to EN ISO 345 Standards.



Safety Trainers SSF04

Price/Pair RND 343.50

Manufactured to EN345. 200J steel toecap. Steel midsole. Oil, petrol, water acid and alkali resistant. Anti-static. Dual density polyurethane/rubber soles.















Weights & Measures CONVERSIONS

C = Centigrade **F** = Fahrenheit ft = Feet g = Gram gal = UK Gallon hp = Horse Power

K = Kelvin kg = Kilogram **km** = Kilometre **Kw** = Kilowatt I = Litre

Ib = Pound mm = Millimetre mtr = Metre oz = Ounce pt = UK Pint yd = Yard

To Convert From Imperial	To Metric	Multiply By
°F	°C	°C=(°F-32) x 5/9
°F	°K	°K=°C + 271.3
ft	mtr	0.3048
ft ²	mtr ²	0.092903
ft ³	mtr ³	0.028317
ft-lbs	kg-m	0.13826
ft-tons	tonne-mtr	0.3097
gal	ltr	4.54609
gal/ft ²	ltr/m ²	48.905
grains/gal	gm/ltr	0.01425
hp	kw	0.7457
in	mm	25.40
in ²	cm ²	6.4516
in ²	mm ²	645.16
in ³	cm3 (cc)	16.3871
in-tons	kg-m	25.8
lb	kg	0.45360
lb/ft	kg/m	1.488
lb/ft2	kg/m ²	4.883
lb/ft ³	kg/m ³	15.020
lb/gall	kg/ltr	0.09983
lb/in² (PSI)	kg/cm ²	0.07037
lb/in² (PSI)	kg/mm²	0.0007037
Ib/in ² (PSI)	kg/mtr ²	703.7
lb/mile	kg/km	0.2818
lb/yd	kg/m	0.496
lb/yd ³	kg/m ³	0.5933
nautical mile	km	1.8532
miles	km	1.60934
miles ²	km ²	2.58999
OZ	g	28.3495
pt	Îtr	0.568261
tons	tonnes (1000kg)	1.01605
tons/ft	kg/m	3333.33
tons/ft ²	tonnes/m ²	10.936
tons/in ²	kg/mm²	1.575
tons/in ²	n/mm²	15.444
tons/yd	kg/m	1111.11
tons/yd ²	tonnes/m ²	1.215
tons/yd ³	tonnes/m ³	1.329
vd	mtr	0.9144
yd ²	mtr ²	0.836127
yd ³	mtr ³	0.764555

To Convert From Metric	To Imperial	Multiply By
°C	°F	°F=(°Cx9/5)+32
°K		°F=(°K-271.3)x1.8+32
cm ²	in ²	0.155
cm ³ (cc)	in ³	0.06102
g	OZ	0.035274
gm/ltr	grains/gal	70.156
kg	lb	2.2046
kg/cm ²	lb/in² (PSI)	14.223
kg/km	lb/mile	3.548
kg/ltr	lb/gal	10.022
kg/m	lb/ft	0.672
kg/m	lb/yd	2.016
kg/m	tons/ft	0.0003
kg/m	tons/yd	0.0009
kg/m ²	lb/ft ²	0.2048
kg/m ³	lb/ft ³	0.0624
kg/m ³	lb/yd ³	1.686
kg/mm ²	lb/in² (PSI)	1421.06
kg/mm ²	tons/in²	0.635
kg/mtr ²	lb/in² (PSI)	0.00142
	in-tons	0.03875
kg-m	ft-lbs	7.233
kg-m km	nautical miles	0.5396
		0.62137
km	miles	0.82137
km ²	miles ²	0.38610
kw	hp	1.341 0.21997
ltr	gal	
ltr	ptpt	1.75975 0.0204
ltr/m ²	gall/ft ²	
mm	<u>in</u>	0.03937
mm ²	in ²	0.00155
mtr	yd	1.09361
mtr	ft	3.28084
mtr ²	yd ²	1.19599
mtr ²	ft ²	10.76391
mtr ³	yd ³	1.30795
mtr ³	ft³	35.31467
N/mm ²	tons/in ²	0.06475
tonne-m	ft-tons	3.229
tonnes (1000kg)	tons	0.9842
tonnes/m ²	tons/ft ²	0.0914
tonnes/m ²	tons/yd ²	0.823
tonnes/m ³	tons/yd ³	0.752
Apothecaries' Weight Apothecaries' Fluid Measure		

Metric Weight **Metric Surface Area** 10 Milligrams 1 Centigram 1 Centiares 1 samtr 10 Centigrams 1 Decigram 10 Centiares 1 Deciare 1 Are, (100 sq metres) 10 Decigrams 1 Gram 10 Deciares 10 Grams Decagram 10 Ares 1 Dekare 10 Decagram Hectogram 10 Dekares 1 Hectare (10,000 sqmtr) 10 Hectograms 1 Kilogram 100 Hectares 1 Sq km 10 Kilograms 1 Myriagram **Metric Length Metric Capacity** 10 Millimetres 1 Centimetre

10 Millilitres 1 Centilitre 10 Centilitres 1 Decilitre 10 Decilitres 1 Litre 1 Decalitre 10 Litres 10 Decalitres 1 Hectolitre 10 Hectolitres 1 Kilolitre

Apothecaries' Fluid Measure Apothecaries' Weight Used for Dispensing Drugs, etc. 60 Minims 1 Dram 20 Grains 1 Scruple Drams Ounce 3 Scruples 1 Dram 20 Ounces Pint 8 Drams 1 Ounce 8 Pints 1 Gallon 12 Ounces 1 Pound

Troy Weight

Grains)

24 Grains 1 Pennyweight 1 Ounce (480 Grains) 20 Pennyweight 12 Ounces 1 Pound (5760

Diamonds and Pearls are weighed by Carats, of 4 grains each (equal to 3.2 Troy grains). The Troy ounce is equal to 150 Diamond Carats. Gold, when pure, is 24 Carats fine; if it contains one part alloy it is said to be 23 Carats, and so on.

1 Pint

Imperial Weight (Avoirdupois)

10 Centimetres

10 Decimetres

10 Decametres

10 Kilometres

10 Hectometres

10 Meters

Used for General Merchandise 1 Ounce 16 Drams (437¹/₂ Grains Troy) 1 Pound 16 Ounces (7000 Grains Troy) 14 Pounds 1 Stone 28 Pounds 1 Quarter 100 Pounds 1 Cental 1 Hundredweight 4 Quarters (112 Pounds) 2000 Pounds 1 Short Ton 20 Hundredweight 1 Ton (2240 Pounds)

1 Decimetre

1 Decametre

1 Hectometre

1 Myriametre

1.094 Yards, 39.371in

1 Kilometre

1 Metre

Avoirdupois pounds are greater than Troy in the proportion of 17 to 14 approx; Troy ounces are greater than Avoirdupois in the proportion of 79 to 72 approx.

Imperial Surface Area

144 Square inches 1 Square foot 9 Square feet 1 Square yard 301/4 Square yards 1 Square pole 40 Square poles 1 Rood 4 Roods 1 Acre 640 Acres 1 Square mile

7.92 inches is equal to one hundredth of a "Gunter's Chain" (22 yards) which is (was) commonly used by surveyors. An "Engineer's link" is equal to 12 inches and a chain is therefore 331/3 yards (100 feet)

Imperial Cubic Capacity

1728 Cubic Inches 1 Cubic Foot 27 Cubic Feet 1 Cubic Yard 5 Cubic Feet 1 Barrel Bulk 40 Cubic Feet 1 Ton Shipping 40 Cubic Feet 1 Load Hard Timber 50 Cubic Feet 1 Load Foreign Fir

Imperial Length Imperial Capacity Used for Liquids and Dry Goods 3 Barleycorns 1 Inch 1 Palm 4 Gills 3 Inches 4 Inches 1 Hand 2 Pints 7.92 Inches 1 Link 4 Quarts 9 Inches 1 Span 2 Gallons 12 Inches Foot 4 Pecks 18 Inches 1 Cubit 8 Bushels 30 Inches 1 Pace 3 Feet 1 Yard 37.2 Inches 1 Scottish Ell 45 Inches English Ell 1 Geometrical Pace 5 Feet 6 Feet 1 Fathom $5^{1/2}$ Yards 1 Pole 4 Poles 1 Chain water 100 Links 1 Chain

1 Furlong

1 Furlong

Cable

1 League

1 Nautical Mile 1.1515 land Miles

1 Mile (land)

1 Nautical Mile

1 Nautical Mile

1 Quart 1 Gallon 1 Peck 1 Bushel 1 Quarter 5 Quarters 1 Load 1 Chaldron 36 Bushels A bushel of wheat on an average weighs 60 pounds; of barley, 47 pounds; of oats, 40 pounds. The gallon contains 10 pounds avoirdupois of distilled

Decimal Capacity

		,	
Pints	Gallon	Cub.Ft.	Litres
1	0.125	0.0200	0.568
8	1.000	0.1604	4.544
16	2.000	0.3208	9.082

3 Miles (land)

10 Chains

220 Yards

608 Feet

8 Furlongs

10 Cables

1 Knot